HUBBELL **Power Systems**

Hook, Suspension Ball

By ANDERSON Catalog # HB30

Suspension hooks are used to attach ball and socket or clevis insulators directly to the tower attachment pad. All hooks are of the self-locking design.

Features

- Self-locking design
- Ultimate Strength is 30,000 lbs. (133 Kn)
- 2 inch length
- Material: Galvanized Forged Steel
- For use with ANSI Class 52-3 and 52-5 clevis type insulators per ANSI Spec. C29.2-71.

General

Catalog Number	HB30
Material	Steel
Number of Bolt Holes	0
Series	HB Series
Strength Rating - Ultimate	30000 lb
Strength Rating - Ultimate	0 lb
Body	
UPC	096359315292

Dimensions

Assembly Rating (Ultimate) 0 lb Diameter - Bolt 0 in Diameter - Pin 0 in Dimensions 3.188 in x 3 in x 0.719 in



Height	0.719 in
Insulator Throat Diameter -	0 in
Maximum	
Insulator Throat Diameter -	0 in
Minimum	
Insulator Throat Diameter	0 - 0
Range	
Length	3.188 in
Length - Coupling	2 in
Length - Pin	0 in
Maximum Adjustment	0 in
Ring Height	0 in
Weight	1.372 lb
Width	3 in
Conductor Related	
Conductor Diameter -	0 in
Maximum	
Conductor Spacing	0 in

Product Assets

Catalogs - Transmission Connectors Catalog - Full Sales Drawings - HB30 Specifications - HB30

