

DUCK BILL GROUND CLAMPS



1810-2



4706-4



10476



10478

|          | CAT NO | DESCRIPTION   | MAIN LINE RANGE<br>MAXIMUM<br>MINIMUM         | MAXIMUM<br>SIZE<br>CABLE | MAXIMUM<br>FAULT CURRENT<br>RATING | TERMINAL<br>TYPE | LBS |
|----------|--------|---------------|---|--------------------------|------------------------------------|------------------|-----|
| BRONZE   | 1810-2 | SMOOTH JAWS   | 336.4 MCM ACSR / .75 DIA<br>6 SOLID / .16 DIA | 2/0                      | 27KA@15 CYCLES<br>20KA@30 CYCLES   | BOLTED           | 1.1 |
| ALUMINUM | 4706-4 | SERRATED JAWS | 954 MCM ACSR / 1.15 DIA<br>6 SOLID / .16 DIA  | 4/0                      | 43KA@15 CYCLES<br>30KA@30 CYCLES   | BOLTED           | 1.5 |
|          | 10476  | SMOOTH JAWS   | 900 ACSR 556 MCM / 1.16 DIA                   |                          |                                    | THREADED         | 1.5 |
|          | 10477  | SERRATED JAWS | 6 SOLID / .162 DIA                            |                          |                                    | THREADED         | 1.5 |
|          | 10478  | SMOOTH JAWS   |   |                          |                                    | BOLTED           | 1.5 |

**GROUNDING CABLE**

- Copper Stranded
- Tough jacket material
- Fine strands for flexibility
- Easy to strip for preparation
- Cable is available in a yellow neoprene jacket or a clear pvc jacket



**13698**



**13701**

| CAT NO   | SIZE | STRANDS* | WIRE DIAMETER INCHES | OVERALL DIAMETER INCHES | APPROXIMATE WEIGHT PER 1,000 FEET |
|--|------|----------|----------------------|-------------------------|-----------------------------------|
| <b>YELLOW JACKET COPPER GROUND CABLE</b>   |      |          |                      |                         |                                   |
| 9206   | #2   | 665      | .320                 | .435                    | 263                               |
| 9201   | 1/0  | 1064     | .410                 | .570                    | 414                               |
| 13698  | 2/0  | 1323     | .470                 | .620                    | 504                               |
| 9228   | 4/0  | 2107     | .590                 | .740                    | 775                               |
| <b>CLEAR JACKET COPPER GROUND CABLE</b>  |      |          |                      |                         |                                   |
| 13692  | #2   | 665      | .350                 | .530                    | 300                               |
| 21263  | 1/0  | 1064     | .450                 | .640                    | 475                               |
| 13701  | 2/0  | 1323     | .490                 | .700                    | 565                               |
| 21264  | 4/0  | 2107     | .620                 | .840                    | 856                               |
| *NOTE: STRANDS SHOWN ABOVE ARE PER ASTM 855, ALL HASTINGS GROUNDING CABLE IS MANUFACTURED TO ASTM STANDARDS. (STRANDING MAY VARY WITH MANUFACTURER.) |      |          |                      |                         |                                   |

| FAULT CURRENT RATING TABLE FOR GROUNDING CABLE |   |           |
|--|---|-----------|
| GROUND CABLE SIZE AWG                          | RATINGS IN AMPERES SYMMETRICAL RMS 60 HERTZ |           |
|  | 15 CYCLES                                   | 30 CYCLES |
| #2   | 14,500                                      | 10,000    |
| 1/0  | 21,000                                      | 15,000    |
| 2/0  | 27,000                                      | 20,000    |
| 4/0  | 43,000                                      | 30,000    |