



\* Representative image

## Anchor, Lead/Adapter, SS5, 10/12 X 3.5ft Tripleye

by CHANCE Utility  
Catalog ID: 126543EJ

Square Shaft (SS 5) Lead Section, 3' 6" (914 mm) long with 10" (254 mm) -12" (304 mm) Helices with Guy Adapter Tripleye in separate box.

- Square Shaft Lead Sections are assembled to Square Shaft Extension with through bolt.
- The helical shaped plates do not auger into the soil but rather screw into it with minimal soil disturbance
- Hot dipped galvanized per ASTM A153
- Capacity of anchor can be determined by measuring installation torque

## Product Details

### General

Coating	Galvanized
Eye Nut Style	Tripleye
Number of Helices	2
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength. Note: Pulling Eye Rated: 12,000 lbs. Guy wire should not be attached to pulling eye.
Tensile Strength	70000 lb
Torque Rating	5500 ft-lbs
Type	Lead Sections
UPC	096359068556

### Dimensions

Anchor Helix Diameter(s)	10 in - 12 in
Length	42.000 in
Weight	70.600 lb

### Logistics

Standard Package	1
------------------	---

For further technical assistance, please contact us

#### Domestic Customer Service

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: hpscsc@hubbell.com

#### International Customer Service

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: hpsintlcs@hubbell.com