




-NOTES-

1. HOT DIP GALVANIZE PER ASTM A153-(LATEST REV).
2. SHARPENED LEADING EDGE.
3. HELIX MATERIAL-HOT ROLLED LOW CARBON STEEL SHEET, STRIP OR PLATE PER ASTM A572;OR A1018, MINIMUM YIELD STRENGTH = 50 KSI 12" AND 14" HELIX IS GRADE 50, 3/8" THICK. 15" HELIX IS GRADE 80, 3/8" THICK.
4. ADD USA SUFFIX TO CATALOG NUMBER FOR BUY AMERICA ITEMS. PURCHASERS OF BUY AMERICA ITEMS WILL BE PROVIDED A DATED CERTIFICATE OF COMPLIANCE TO SPECIFIC BUY AMERICA PROVISIONS IF REQUESTED AT THE TIME OF ORDER. CONTACT HUBBELL POWER SYSTEMS CUSTOMER SERVICE FOR DETAILS.

CAT NO.	DESCRIPTION	"L"	"L2"	"H"
12655J	S. S ANCHOR EXTENSION	40.75	37.53	12"
12656J	S. S ANCHOR EXTENSION	60.50	57.28	12"
12656N	S. S ANCHOR EXTENSION	60.50	57.28	14"
12655N	S. S ANCHOR EXTENSION	40.75	37.53	14"
C1100937	S. S ANCHOR EXTENSION	123.00	119.78	15"

CHANCE CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.		 HUBBELL POWER SYSTEMS	
		HELICAL EXTENSION	
SIZE B	DWG NO. SA12655J	CAT / PART / ASSY NO. SEE CHART	REV R
DO NOT SCALE THIS DRAWING	DRN BY JCA	DATE 7/24/09	SHEET 1/2
		 THIS SYMBOL IDENTIFIES CRITICAL FEATURES	