



Representative Image

## Catalog No. IKL55

**Description:** AL SERV ENTR SPLICE A:4/0 B:1-2 5.5

**UPC No** 783786050291

**Home > Medium Voltage Utility Solutions > Blackburn > Wire or cable compression splice**

Aluminum 4 inch Service Entrance Compression Splice for Wire Range - Black End: 3/0 ASCR, 3/0 STR, 4/0 CPT, 3/0 CPR. Red End: #2 ASCR, #1-#2 STR, #1 SOL, #1 CPR. Installing Dies: TX 249 840 (EEI 11A). Compound and Capped. includes 5-7/16 inch Sleeve

### Descriptors

Category	Wire or cable compression splice
Special Features	Pre-insulated for fast, easy installation of large home or commercial service entrances. Concave polyethylene end caps seal out dirt, but are easily pierced when inserting conductor.
Application	For Combinations of Aluminum-to-Aluminum and Aluminum-to-Copper Conductors. Use as a low tension reducing sleeve for Insulated Conductor.

### Specifications

Connection	Compression
Conductor Range	End A: 3/0 ACSR , 3/0 STR , 3/0 COMPR , 4/0 COMPT. End B: #2 ACSR , #1 to #2 STR , #1 COMPR , #1 SOL
Number Of Conductors	2
Material	Aluminum
Insulation	yes
Mounting	None
Environmental Conditions	All Seasons / Conditions

### Classifications

Brand Name	Blackburn
Standard	RUS Listed. Passes the Requirements of ANSI C119.4 RUS Listed. Passes the Requirements of ANSI C119.4

### Dimensions

Size	Splice 4 inch, Sleeve 5-1/2 inch
------	----------------------------------

### Compliance and Certifications

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant