

**Catalog No. PRS40N****Description: COMP PIN TERM 397 PIGTAIL .625X8****UPC No 783786050482****Home > Medium Voltage Utility Solutions > Blackburn > Wire or cable compression reducer**

Compression Pin Terminal Aluminum, Contax filled for Wire Range 397 18/1, 477 18/1 ASCR, 450-500 MCM, Pigtail: 0.625 x 8, Hydraulic Dies: B20AH, CSA28, EEI 14A, 318, 1064, 1 5/16. Includes Sleeve and End Plug.

Representative Image

Descriptors

| | |
|------------------|--|
| Category | Wire or cable compression reducer |
| Special Features | Sleeves are Highly Conductive Aluminum. Pigtails are Solid Copper, Tin-Plated. Installed with Standard Tools and Dies. Prefilled with Oxide Inhibitor. |
| Application | Designed for use in joining Aluminum Secondaries and Services to Copper Transformer Bushings |

Specifications

| | |
|----------------------|--|
| End Connection | Compression |
| Number Of Conductors | 1 |
| Material | Aluminum Sleeve, Pre-attached Copper Pigtail |
| Finish | Tinplated Pigtail |
| Voltage Rating | 35 kV |
| Insulation | None |
| Mounting | None |

Classifications

| | |
|------------|-----------|
| Brand Name | Blackburn |
|------------|-----------|

Dimensions

| | |
|----------------|---|
| Size | Sleeve Length 5-1/2 inches |
| Conductor Size | 397(18/1) 477(18/1) ASCR AWG , 450 to 500 kcmil |

Compliance and Certifications

| | |
|------------|-----------------------------|
| RoHS | RoHS3 Compliant |
| REACH SVHC | REACH 240 Compliant |
| TSCA | TSCA Section 6(h) Compliant |