



Catalog No. WR139

Description: AL HTYPE COMP CONN 1/0-4ACSR 2/0-3

UPC No 783786100361

Home > Medium Voltage Utility Solutions > Blackburn > Wire connectors

Aluminum Wide Range H-Type Compression Connector Main: 1/0 - 4 ACSR, 2/0 - 3 Str., 2/0 - 2 Sol. Tap: 8 -10 Str., 6 - 10 Sol., Groove C: 12 - 14 Str., 12 -14 Sol. Die: O

Descriptors

Category	Wire connectors
Special Features	Made of 1350 Aluminum Alloy for high strength and high conductivity. Standard Compression tools and dies install all sizes - no special tools needed. Field-proven ribbed design enables excellent connector/conductor contact without distorting the conductor's shape. Fold-in tabs provide tab interlock as tool closes. Prefilled with oxide inhibitor held captive in the rib/connection area.
Application	For Combinations of Aluminum to Aluminum and Aluminum to Copper Conductors.

Specifications

Connection	Compression
Number Of Conductors	3
Material	Aluminum
Insulation	None
Temperature Rating	up to 90 C
Mounting	None
Environmental Conditions	All Seasons / Conditions

Classifications

Brand Name	Blackburn
Standard	RUS Accepted. Complies with ANSI C119.4 Specifications

Dimensions

Size	Length 1-1/2 inch
Wire Size	Main: 1/0 to #4 ACSR or 2/0 to #3 STR or 2/0 to #2 SOL AWG , Tap A: #8 to #10 STR or #6 to #10 SOL AWG , Tap B: #12 to #14 STR or #12 to #14 SOL AWG

Compliance and Certifications

RoHS	RoHS3 Compliant
REACH	REACH 247 Compliant

by ABB

