



## Catalog No. WR279

**Description:** AL HTYPE COMPCONN 2/0-1ACSR 2/0-1

**UPC No** 783786100071

**Home > Medium Voltage Utility Solutions > Blackburn > Wire connectors**

Aluminum Wide Range H-Type Compression Connector, Main: 2/0-1/0 ACSR, 3/0-1/0 Str., 4/0-2/0 Sol. Tap: 2/0-1 ACSR, 3/0-1/0 Str., 3/0-2/0 Sol. Die: D

### Descriptors

Category	Wire connectors
Special Features	Made of 1350 Aluminum Alloy for high strength and high conductivity. Standard Compression tools and dies install all sizes - no special tools needed. Field-proven ribbed design enables excellent connector/conductor contact without distorting the conductor's shape. Fold-in tabs provide tab interlock as tool closes. Prefilled with oxide inhibitor held captive in the rib/connection area.
Application	For Combinations of Aluminum to Aluminum and Aluminum to Copper Conductors.

### Specifications

Connection	Compression
Number Of Conductors	2
Material	Aluminum
Insulation	None
Temperature Rating	up to 90 C
Mounting	None
Environmental Conditions	All Seasons / Conditions

### Classifications

Brand Name	Blackburn
Standard	RUS Accepted. Complies with ANSI C119.4 Specifications RUS Accepted. Complies with ANSI C119.4 Specifications

### Dimensions

Size	Length 1-13/16 inch
Wire Size	Main: 2/0 to #1 ACSR or 3/0 to 1/0 STR or 4/0 to 2/0 SOL AWG , Tap: 2/0 to #1 ACSR or 3/0 to 1/0 STR or 3/0 to 2/0 SOL AWG

### Compliance and Certifications

RoHS	RoHS3 Compliant
REACH	REACH 247 Compliant

**by ABB**

