

Account Details

| Account No. | 9036149_USS6_10_10 |
|-------------|---|
| Account | KENTUCKY ASSOC OF ELEC COOPS |
| Address | KENTUCKY ASSOC OF ELEC COOPS, 4300 CHAMPIONS TRACE LN, , LOUISVILLE, Kentucky, 40218 United States |
| Sales Org. | ABB Installation Products USA |
| Sales | Distribution |
| Currency | USD |
| As on Date | 11-30-2023 |
| | |

Catalog No. 161LRJS-B-5220

Product Details



UPC: 075114241298

Details: 15KV, 200 Amp, Loadbreak Elbow with Sealing Jacket, Cable Insulation Diameter 0.635 inch to 0.905 inch. Bi-Metal Compression Lug. Conductor Size AWG Compressed Stranded #2/Solid #1/mmSquared 33.62.

Product Details

Details

| Catalog No. | 161LRJS-B-5220 | |
|------------------------|---------------------------------|--|
| Description | 15KV LB ELBOW W- JACKET SEAL | |
| Std. Package Weight | 2.210 LB | |
| Product Family | 9CO | |
| Restock Fee | | |
| Customer Reference No. | | |
| Brand Name | ELASTIMOLD | |
| Minimum Order Qty. | 1 | |

| UPC | 075114241298 | |
|-------------------|---------------|--|
| GSA Compliance | No | |
| Discount Schedule | 9C | |
| CCC | | |
| Currency | USD | |
| Notes | | |
| Package Qty. | 1 | |
| Country of Origin | United States | |
| | | |

| General Characteristics | | Dimensions and Classifications | | |
|-----------------------------|---|--------------------------------|------------------------|--|
| Category | Electrical connector assembly | Brand Name | Elastimold | |
| Туре | Loadbreak Elbow Connector and Jacket Seal | Standard | ANSI/IEEE Standard 386 | |
| Special Features | Fully Shielded, Fully Submersible Molded Rubber Housing, 100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Provision for Hot Stick Operation. Provision for Ground Wire Connection. Built in Cable Jacket Seal. | | | |
| Application | The 161LRJS is designed for Connecting to and Operating 15kV Class, 200 Amp Distribution apparatus. It Provides a Convenient Method to Connect/Disconnect Cable and Equipment on Power Distribution Systems. | | | |
| Conductor Range | #2 STR/COMPR AWG , #1 SOL/COMPT AWG | | | |
| Material | Housing - EPDM Rubber | | | |
| Color | Black | | | |
| Voltage Rating | 15 kV | | | |
| Amperage Rating | 200 A | | | |
| Insulation | Yes, EPDM Rubber | | | |
| Temperature Rating | -40 to +65 C | | | |
| Environmental Conditions | Products are designed and constructed for all applications including Padmount, Subsurface, Vault, Indoor, Outdoor, Direct Sunlight, Direct Buried and Continuously Submerged in Water. | | | |

by ABB electrification.us.abb.com

Created On: 11/30/2023