




## GAR3906, Mech Ground Conn, Conductor to Water Pipe

By Burndy  
Catalog # [GAR3906](#)

Mechanical Grounding Connector, Conductor to Water Pipe, 4-4/0 AWG, 6" Pipe, 3/8" Stud



## Features

- Cable clamp swivels at 90°, permits parallel grounding of one pipe on a 90° cable run for grounding several parallel pipes
- One-wrench installation for simplified installation
- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- Provides quality assurance to recognized industry NEC standards from an independent part

## Application

For Connecting A Small To Medium Range Copper Ground Conductor To Water Pipe As Well As Structural And Reinforcing Rod Shapes, Direct Burial Cables

## Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

## Conductor

Conductor - Pipe or Round Tube Size	6 in
Conductor - Copper Str Size	<ul style="list-style-type: none"><li>• 4</li><li>• 3</li><li>• 2</li><li>• 1</li><li>• 1/0</li><li>• 2/0</li><li>• 3/0</li><li>• 4/0</li></ul>
Conductor - Copper Solid Size Range	4 AWG - 4/0 AWG
Conductor - Copper Str Size Range	4 AWG - 4/0 AWG

Conductor - Copper Tube Std Size Range	6
Conductor - Copper Tube Std Size	6

## Dimensions

Package Height	0.000 in
Dimension - Height mm	215.9 mm
Dimension - Height inch	8.50 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - Outside Diameter inch	6.62 in
Dimension - Width mm	219 mm
Dimension - Width inch	8.62 in
Dimension - B Length inch	1.75 in
Dimension - Length Overall inch	1.75 in

## Force Related

Installation Torque Recommended in-lb	200 lb-in
---------------------------------------	-----------

## General

Material - Hardware Plated	Galvanized Steel N
Sub Brand	MECHANICAL CONNECTOR
UPC	781810234051
Type	GAR3902
U Bolt Type	1027G
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810234051
UPC 14 Digit GTIN	00781810234051

## Logistics

Minimum Pack Quantity	1
Pallet Quantity	546
Carton Quantity	6

## Product Assets

[Catalog \[English\]](#)



A Hubbell brand