


DRAWING NO. SD052025		7		6		5		4		3		2		1															
CATALOG NUMBER	CONDUCTOR RANGES (CONCENTRIC & COMPRESSED)													DIMENSIONS															
	A							AA																					
	ACSR		ALUMINUM		COPPER		COLOR CODE	ACSR		ALUMINUM		COPPER		COLOR CODE	B MIN.	L	O.D.												
SIZE	STR.	SIZE	STR.	SIZE	STR.	SIZE		STR.	SIZE	STR.	SIZE	STR.																	
YSU6W6W	---	---	#8 STR. (.146 DIA.) [4MM DIA.] #6 SOL. (.162 DIA.) [4MM DIA.] #8 COMPT (.135 DIA.) [3MM DIA.]	7 1 --	#8 STR. (.146 DIA.) [4MM DIA.] #6 SOL. (.162 DIA.) [4MM DIA.]	7 1	GREEN	---	---	#8 STR. (.146 DIA.) [4MM DIA.] #6 SOL. (.162 DIA.) [4MM DIA.] #8 COMPT (.135 DIA.) [3MM DIA.]	7 1 --	#8 STR. (.146 DIA.) [4MM DIA.] #6 SOL. (.162 DIA.) [4MM DIA.]	7 1	GREEN	 .87 [22]	 2.00 [51]	 .65 [17]												
YSU4W8W	 #6 (.198 DIA.) [5MM DIA.] 	 6-1 	 #5 STR. (.206 DIA.) [5MM DIA.] #6 STR. (.184 DIA.) [5MM DIA.] #4 SOL. (.204 DIA.) [5MM DIA.] #4 COMPT (.214 DIA.) [5MM DIA.] 	7 7 1 --	 #5 STR. (.206 DIA.) [5MM DIA.] #6 STR. (.184 DIA.) [5MM DIA.] #4 SOL. (.204 DIA.) [5MM DIA.] 	7 7 1	BLUE	---	---	#10 STR. (.116 DIA.) [3MM DIA.] #8 SOL. (.129 DIA.) [3MM DIA.]	7 1	#10 STR. (.116 DIA.) [3MM DIA.] #8 SOL. (.129 DIA.) [3MM DIA.]	7 1	BROWN															
YSU4W6W										#8 STR. (.146 DIA.) [4MM DIA.] #6 SOL. (.162 DIA.) [4MM DIA.] #8 COMPT (.135 DIA.) [3MM DIA.]	7 1 --	#8 STR. (.146 DIA.) [4MM DIA.] #6 SOL. (.162 DIA.) [4MM DIA.]	7 1	GREEN															
YSU4W4W										#6 STR. (.184 DIA.) [5MM DIA.] #4 SOL. (.204 DIA.) [5MM DIA.] #5 STR. (.206 DIA.) [5MM DIA.] #4 COMPT (.214 DIA.) [5MM DIA.]	7 1 7 --	#6 STR. (.184 DIA.) [5MM DIA.] #4 SOL. (.204 DIA.) [5MM DIA.] #5 STR. (.206 DIA.) [5MM DIA.]	7 1 7 --	BLUE															
YSU2W10W										 #4 (.250 DIA.) [6MM DIA.] #4 (.257 DIA.) [6MM DIA.] 	 6-1 7-1 	 #4 STR. (.232 DIA.) [6MM DIA.] #2 SOL. (.258 DIA.) [7MM DIA.] #3 STR. (.260 DIA.) [7MM DIA.] 	7 1 7	 #4 STR. (.232 DIA.) [6MM DIA.] #2 SOL. (.258 DIA.) [7MM DIA.] #3 STR. (.260 DIA.) [7MM DIA.] 				7 1 7	ORANGE	---	---	#12 STR. (.092 DIA.) [2MM DIA.] #10 SOL. (.102 DIA.) [3MM DIA.]	7 1	#12 STR. (.092 DIA.) [2MM DIA.] #10 SOL. (.202 DIA.) [3MM DIA.]	7 1	---			
YSU2W8W	#10 STR. (.116 DIA.) [3MM DIA.] #8 SOL. (.129 DIA.) [3MM DIA.]	7 1	#10 STR. (.116 DIA.) [3MM DIA.] #8 SOL. (.129 DIA.) [3MM DIA.]	7 1	BROWN																								
YSU2W6W	#8 STR. (.146 DIA.) [4MM DIA.] #6 SOL. (.162 DIA.) [4MM DIA.] #8 COMPT (.135 DIA.) [3MM DIA.]	7 1 --	#8 STR. (.146 DIA.) [4MM DIA.] #6 SOL. (.162 DIA.) [4MM DIA.]	7 1	GREEN																								
NOTES:																													
 BARREL IS PARTIALLY FILLED WITH PENETROX™ AND SEALED IN POLYBAG.																													
2. SCRATCH BRUSHING OF ALUMINUM CONDUCTORS, BEFORE MAKING INSTALLATIONS, IS RECOMMENDED.																													
3. THE END OF THE LINKIT™ THAT ACCOMMODATES STRANDED CABLE WILL ALSO ACCOMMODATE THE SAME SIZE NEUTRAL CONDUCTOR OF COPPER OR ALUMINUM SERVICE ENTRANCE CABLE. EXAMPLE: THE #6 NEUTRAL OF SERVICE ENTRANCE CABLE CAN BE ACCOMMODATED IN THE LINKIT™ ELEMENT THAT ACCOMMODATES #6 STR. CABLE.																													
 TWO CRIMPS MADE SIMULTANEOUSLY.																													
 THESE LINKITS™ CAN BE INSTALLED WITH KEARNEY TOOLS USING 5/8" GROOVE.																													
 ALL CONNECTORS ARE COLOR CODED TO PERMIT VISUAL CONDUCTOR RANGE IDENTIFICATION.																													
 CATALOG #PT6515 ADAPTOR IS REQUIRED TO USE "U" DIES IN Y45 SERIES TOOLS.																													
 CATALOG #PUADP-1 ADAPTOR IS REQUIRED TO USE "U" DIES IN Y46 SERIES TOOLS.																													
9. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS ROUNDED OFF TO THE NEAREST MILLIMETER, UNLESS OTHERWISE NOTED, AND ARE FOR REFERENCE ONLY.																													
<table><tr><td>REV</td><td>DATE</td><td>DESCRIPTION</td><td>ECO</td><td>BY</td><td>C/H/K</td></tr><tr><td>B</td><td>05/08/2017 00:00:00 AM</td><td>LOGO UPDATE</td><td>46695</td><td>BK</td><td>MB</td></tr></table>																		REV	DATE	DESCRIPTION	ECO	BY	C/H/K	B	05/08/2017 00:00:00 AM	LOGO UPDATE	46695	BK	MB
REV	DATE	DESCRIPTION	ECO	BY	C/H/K																								
B	05/08/2017 00:00:00 AM	LOGO UPDATE	46695	BK	MB																								
8		7		6		5		4		3		2		1															

CATALOG NUMBER	BURNDY INSTALLATION TOOLING (# CRIMPS PER END)						
	DIE INDEX	MECHANICAL			HYDRAULIC		
		ONE HAND TOOL	OUR840	MD6 MD7	Y35, Y39 Y750, BAT35 BAT750	 Y46	 Y45
YSU6W6W THRU YSU25A25A	 BG 243 5/8	OH25(1)	X-NBG(2) 	 W-BG(2) BG FIXED GROOVE(3) W243(2)	 U-BG(2) U243(1)	U243(1)	U243(1)

TO ORDER BURNDY® PRODUCTS CALL UNITED STATES 1-800-346-4175 (LONDONDERRY, NH) CANADA: 1-800-361-6975 (QUEBEC) 1-800-387-6487 (ALL OTHER PROVINCES) FOR PRODUCT INFO: http://www.burndy.com		LINKITS™ (ALUMINUM)		
		ITEM NO: N/A		
		CAT. NO: SEE (TABLE)		
		DRAWN BY: MJM 08/10/62		
		CHECKER: ERD 08/10/62		
DSN APPVL: ESR 08/12/62				
MFG APPVL: N/A				
QA APPVL: D.VARIO 07/13/95				
MKT APPVL: L.HERRON 07/10/95				
PROD FAM: --				
PROJECT #: --				
DOCUMENT TYPE: Sales				
REL LEVEL: Released				

DRAWING NO		REV
SD052025		B
SHEET 1 OF 4		

SCALE: 1:1

DRAWING NO. SD052025		7		6		5		4		3		2		1							
CATALOG NUMBER	CONDUCTOR RANGES (CONCENTRIC & COMPRESSED)													DIMENSIONS							
	A							AA													
	ACSR		ALUMINUM		COPPER		COLOR CODE	ACSR		ALUMINUM		COPPER		COLOR CODE	B MIN.	L	O.D.				
	SIZE	STR.	SIZE	STR.	SIZE	STR.		SIZE	STR.	SIZE	STR.	SIZE	STR.								
YSU2W4W	#4 (.250 DIA.) [6MM DIA.] #4 (.257 DIA.) [6MM DIA.]	↑ 6-1 7-1 ↓	↑ 7 1 7 ↓	↑ #4 STR. (.232 DIA.) [6MM DIA.] #2 SOL. (.258 DIA.) [7MM DIA.] #3 STR. (.260 DIA.) [7MM DIA.]	↑ 7 1 7 ↓	↑ #4 STR. (.232 DIA.) [6MM DIA.] #2 SOL. (.258 DIA.) [7MM DIA.] #3 STR. (.260 DIA.) [7MM DIA.]	↑ ORANGE ↓	↑ #6 (.198 DIA.) [5MM DIA.]	6-1	↑ #6 STR. (.184 DIA.) [5MM DIA.] #4 SOL. (.204 DIA.) [5MM DIA.] #5 STR. (.206 DIA.) [5MM DIA.] #4 COMPT (.214 DIA.) [5MM DIA.]	7 1 7 --	↑ #6 STR. (.184 DIA.) [5MM DIA.] #4 SOL. (.204 DIA.) [5MM DIA.] #5 STR. (.206 DIA.) [5MM DIA.]	7 1 7	BLUE	↑ .87 [22]	↑ 2.00 [51]	↑ .65 [17]				
YSU2W4WV																					
YSU2W2W																					
YSU2R8W	#2 (.316 DIA.) [8MM DIA.] #2 (.325 DIA.) [8MM DIA.]	↑ 6-1 7-1 ↓	↑ 7 7 -- -- ↓	↑ #1 SOL. (.289 DIA.) [7MM DIA.] #1 STR. (.328 DIA.) [8MM DIA.] #2 STR. (.292 DIA.) [7MM DIA.] #1 COMPT (.299 DIA.) [8MM DIA.] #2 COMPT (.268 DIA.) [7MM DIA.]	↑ 7 7 3 ↓	↑ #1 STR. (.328 DIA.) [8MM DIA.] #2 STR. (.292 DIA.) [7MM DIA.] #2 STR. (.320 DIA.) [8MM DIA.]	↑ RED ↓	↑ ---	---	↑ #10 STR. (.116 DIA.) [3MM DIA.] #8 SOL. (.129 DIA.) [3MM DIA.]	7 1	↑ #10 STR. (.116 DIA.) [3MM DIA.] #8 SOL. (.129 DIA.) [3MM DIA.]	7 1	BROWN	↑ .87 [22]	↑ 2.00 [51]	↑ .65 [17]				
YSU2R6W																					
YSU2R4W																					
YSU2R4WBAG100																					
YSU2R2W																					
YSU2R2WNP																					
YSU2R2R																					
NOTES:																					
▶ BARREL IS PARTIALLY FILLED WITH PENETROX™ AND SEALED IN POLYBAG.																					
2. SCRATCH BRUSHING OF ALUMINUM CONDUCTORS, BEFORE MAKING INSTALLATIONS, IS RECOMMENDED.																					
3. THE END OF THE LINKIT™ THAT ACCOMMODATES STRANDED CABLE WILL ALSO ACCOMMODATE THE SAME SIZE NEUTRAL CONDUCTOR OF COPPER OR ALUMINUM SERVICE ENTRANCE CABLE. EXAMPLE: THE #6 NEUTRAL OF SERVICE ENTRANCE CABLE CAN BE ACCOMMODATED IN THE LINKIT™ ELEMENT THAT ACCOMMODATES #6 STR. CABLE.																					
▶ TWO CRIMPS MADE SIMULTANEOUSLY.																					
▶ THESE LINKITS™ CAN BE INSTALLED WITH KEARNEY TOOLS USING 5/8" GROOVE.																					
▶ ALL CONNECTORS ARE COLOR CODED TO PERMIT VISUAL CONDUCTOR RANGE IDENTIFICATION.																					
▶ CATALOG #PT6515 ADAPTOR IS REQUIRED TO USE "U" DIES IN Y45 SERIES TOOLS.																					
▶ CATALOG #PUADP-1 ADAPTOR IS REQUIRED TO USE "U" DIES IN Y46 SERIES TOOLS.																					
9. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS ROUNDED OFF TO THE NEAREST MILLIMETER, UNLESS OTHERWISE NOTED, AND ARE FOR REFERENCE ONLY.																					
REV		DATE		DESCRIPTION		ECO		BY		C'N'K.											
B		05/08/2017 00:00:00 AM		LOGO UPDATION		46695		BK		MB											
8		7		6		5		4		3		2		1							
						TO ORDER BURNDY® PRODUCTS CALL UNITED STATES 1-800-346-4175 (LONDONDERRY, NH) CANADA: 1-800-361-6975 (QUEBEC) 1-800-387-6487 (ALL OTHER PROVINCES) FOR PRODUCT INFO: http://www.burndy.com						LINKITS™ (ALUMINUM) ITEM NO: N/A CAT. NO: YSU-- (TABLE) DRAWN BY: MJM 08/10/62 CHECKER: ERD 08/10/62 DSN APPVL: ESR 08/12/62 MFG APPVL: N/A QA APPVL: D.VARIO 07/13/95 MKT APPVL: L.HERRON 07/10/95 PROD FAM: -- PROJECT #: -- DOCUMENT TYPE: Sales REL LEVEL: Released						SCALE: N/A DRAWING NO SD052025 SHEET 2 OF 4		REV B	

REV	DATE	DESCRIPTION	ECO	BY	C'K'
B	05/08/2017 00:00:00 AM	LOGO UPDATE	46695	BK	MB

TO ORDER BURNDY® PRODUCTS CALL

UNITED STATES
1-800-346-4175 (LONDONDERRY, NH)

CANADA:
1-800-361-6975 (QUEBEC)
1-800-387-6487 (ALL OTHER PROVINCES)


FOR PRODUCT INFO: <http://www.burndy.com>

LINKITSTM (ALUMINUM)

ITEM NO:	N/A
CAT. NO:	YSU-- (TABLE)
DRAWN BY:	MJM 08/10/62
CHECKER:	ERD 08/10/62
DSN APPVL:	ESR 08/12/62
MFG APPVL:	N/A --
QA APPVL:	D.VARIO 07/13/95
MKT APPVL:	L.HERRON 07/10/95
PROD FAM:	--
PROJECT #:	--
DOCUMENT TYPE:	Sales
REL LEVEL:	Released



DRAWING NO	REV
SD052025	B
SHEET 2 OF 4	

DRAWING NO. SD052025		7		6		5		4		3		2		1																				
CATALOG NUMBER	ITEM NO	CONDUCTOR RANGES (CONCENTRIC & COMPRESSED)												DIMENSIONS																				
		A						AA																										
		ACSR		ALUMINUM		COPPER		6	COLOR CODE	ACSR		ALUMINUM		COPPER		6	COLOR CODE	B MIN.	L	O.D.														
SIZE	STR.	SIZE	STR.	SIZE	STR.	SIZE	STR.			SIZE	STR.	SIZE	STR.																					
YSU25R6W	168378	 1/0 (.398 DIA.) [10MM DIA.] 	6-1	 1/0 STR. (.368 DIA.) [9MM DIA.] 2/0 COMPT (.376 DIA.) [10MM DIA.] 1/0 COMPT (.336 DIA.) [9MM DIA.] 	 7 	 1/0 STR. (.368 DIA.) [9MM DIA.] 	 7 	6	YELLOW	 	---	---	7 1 --	7 1 1	GREEN	 .87 [22]	 2.00 [51]	 5 .65 [17]																
YSU25R4W	168358																						6-1	7 1 7 --	7 1 7 --	BLUE								
YSU25R2W	168339																														6-1 7-1	7 1 7	7 1 7	ORANGE
YSU25R2R	168328																																	
YSU25R25R	168398																														6-1	7	7	YELLOW
												 .87 [22]	 2.00 [51]	 5 .65 [17]																				
NOTES:																																		
1  BARREL IS PARTIALLY FILLED WITH PENETROX™ AND SEALED IN POLYBAG.																																		
2. SCRATCH BRUSHING OF ALUMINUM CONDUCTORS, BEFORE MAKING INSTALLATIONS, IS RECOMMENDED.																																		
3. THE END OF THE LINKIT™ THAT ACCOMMODATES STRANDED CABLE WILL ALSO ACCOMMODATE THE SAME SIZE NEUTRAL CONDUCTOR OF COPPER OR ALUMINUM SERVICE ENTRANCE CABLE. EXAMPLE: THE #6 NEUTRAL OF SERVICE ENTRANCE CABLE CAN BE ACCOMMODATED IN THE LINKIT™ ELEMENT THAT ACCOMMODATES #6 STR. CABLE.																																		
4  TWO CRIMPS MADE SIMULTANEOUSLY.																																		
5  THESE LINKITS™ CAN BE INSTALLED WITH KEARNEY TOOLS USING 5/8" GROOVE.																																		
6  ALL CONNECTORS ARE COLOR CODED TO PERMIT VISUAL CONDUCTOR RANGE IDENTIFICATION.																																		
7  CATALOG #PT6515 ADAPTOR IS REQUIRED TO USE "U" DIES IN Y45 SERIES TOOLS.																																		
8  CATALOG #PUADP-1 ADAPTOR IS REQUIRED TO USE "U" DIES IN Y46 SERIES TOOLS.																																		
9. DIMENSIONS IN BRACKET [] ARE IN MILLIMETERS ROUNDED OFF TO THE NEAREST MILLIMETERS, UNLESS OTHERWISE NOTED, AND ARE FOR REFERENCE ONLY.																																		
REV		DATE		DESCRIPTION		ECO		BY		C' H' K.																								
B		05/08/2017 00:00:00 AM		LOGO UPDATION		46695		BK		MB																								
8		7		6		5		4		3		2		1																				

