



Representative Image

**Catalog No. 168FLR1B5240****Description: 15KV FUSE ELBOW SIZE 1****UPC No 75114214896****Home > Medium Voltage Utility Solutions > Elastimold > Electrical connector assembly**

Molded Current Limiting Fuse Housing, Nominal Fuse Voltage Rating 8.3kV, Fuse Test Port - Two Capacitive Test Ports, Small Housing, Cable Insulation Diameter 0.635 inch - 0.905 inch / 16-23mm, Bi-Metal Conductor size 1/0 AWG Stranded/Compressed, 2/0 AWG Solid/Compact.

**Descriptors**

Category	Electrical connector assembly
Special Features	Full-Range Current-Limiting Fusing with 50kA Interrupting Capability. Hotstick Operable 15kV Loadbreak Elbow Switching.
Application	Protect Light Duty Underground Distribution Systems

**Specifications**

Conductor Range	1/0 STR/COMPR AWG , 2/0 SOL/COMPT AWG
Material	EPDM Rubber
Color	Black
Voltage Rating	8.3 kV
Amperage Rating	200 A
Insulation	Yes, EPDM Rubber
Temperature Rating	-40 to +65 C

**Classifications**

Brand Name	ELASTIMOLD
Standard	IEEE 386, ANSI C37.40, ANSI C37.41, ANSI C37.47

**Dimensions**

Size	Length 16.87 inches from bottom to center of Bushing
------	--