## CHANCE TORQUE INDICATORS



## WIRELESS TORQUE INDICATOR

Using the Wireless Chance® Torque Indicator, you can install screw anchors to a pre-determined torque value, which gives a positive indication of anchor holding capacity in any soil type. The handheld Wireless Data Logger gives real time information on torque while storing for easy download.

The Indicator mounts between the Kelly bar adapter and drive tool (or locking dog assembly). The LCD display is easy to read in full daylight and gives the operator a direct readout of installation torque at all times.

Operational temperature range: -30° to 80°C (-22° to 175° F)

Accuracy: ±500ft-lb at any reading
Torque is measured using strain gauges
No shear pins to replace

Powered by a standard 9V battery

Base unit with wireless display

- Torque is displayed on Base Unit and on Wireless Display
- Multiple Wireless Display units can be linked to Base Unit
- Solid one-piece spool design to withstand bending loads. Top and bottom flange, each provides six holes tapped 1/2"- 13 on a 5-1/4" bolt circle and twelve holes tapped 5/8"- 11 on a 7-5/8" bolt circle.
- Data Logger
  - Torque displayed on Data Logger
  - Torque and GPS data recorded and saved on Data Logger
  - Data downloadable from Data Logger to computer spreadsheet







| Part Number | Description  |
|-------------|--|
| C3031689    | Base Indicator with Wireless Display Screen                                |
| C3031690    | Data Logger  |
| C3031723    | Wireless Display Screen  |
| C3031724    | Indicator Kit (Base Indicator with Wireless Display Screen and Data logger |



## SHEAR PIN TORQUE LIMITER Catalog No. C3030044

For Installing torques up to 10,000 ft.-lb.

Offers: Protection for anchors and installing tools by disconnecting the power when the installing torque reaches a preselected level.

Useable in very rocky soil.

Durable — does not require special storage or handling.

Top and bottom each has six holes tapped  $\frac{1}{2}$ " - 13 on a 5 $\frac{1}{4}$ " bolt circle.

| Catalog Number | Description                                  | Wt., lb. |
|----------------|--|----------|
| C3030044       | Shear Pin Torque Indicator                   | 54       |
| *C3030045      | One Carton of Shear Pins (Approx. 1700 pins) | 50       |
| *T3031420      | One Box of Shear Pins (Approx. 510 pins)     | 15       |

<sup>\*</sup>Each Shear Pin provides 500 ft.-lb. of torque.

HUBBELL

Phone: 573-682-5521 Email: hpsliterature@hubbell.com Web: hubbellpowersystems.com