


# Grip-All, 8 ft

By: CHANCE Lineman Tools & Equipment Catalog # C4030293

GRIPALL - 8FT 7IN, The most versatile tool in a lineworker's hands, the Grip-All stick puts an easy-to-control "finger" on an insulated pole. Although primarily designed for installing hotline and grounding clamps, it serves both overhead and underground circuits with various end fittings. Commonly called a "shotgun," the operating mechanism incorporates a sliding hand grip that opens the hook to grasp a clamp eyescrew and retract it into the tool head. A thumb latch then must be depressed to release the locked hand grip so it can open the hook. While the tool head is of Lexan® for closequarter operations, the worker must maintain recommended working distance solely on the Epoxiglas ™ pole section of the handle as the hook and its actuator are metal parts. Easy to care for, Grip-All sticks do not require field stripping to clean. All insulated parts including the operating rod are outside the main pole, readily accessible to wipe dry. CAUTION: Do not clean the plastic head with solvent.



#### **Features**

- External Operating Rod Type
- Tested per OSHA & ASTM F711
- Versatile tool puts an easy-to-control "finger" on an insulated pole
- Primarily designed for installing hot-line and grounding clamps
- Also serves both overhead and underground circuits with various end fittings
- Operating mechanism (or "shotgun") incorporates a sliding hand grip that opens the hook to grasp a clamp eyescrew and retract it into tool head
- Latch must be depressed to release locked hand grip that opens the hook
- For smooth operation, investment-cast stainless-steel components include Jaw, Jaw Holder, Safety Stop, Lockbar and Latch
- Lexan® tool head is designed for close-quarter operations
- Worker must maintain recommended work distance based solely on the Epoxiglas ™ pole section of the handle, as the hook and its actuator are metal parts
- Easy-care Grip-All Clampsticks do not require field stripping to clean
- All insulated parts, including the operating rod, are outside the main pole, readily accessible to wipe dry

### General

EU RoHS Indicator No

Storage Bag Included? P643-8 (Bag not included.

Must be ordered separately.)

Style Standard UPC 996359018100

### **Dimensions**

Dimensions 107 in x 5 in x 5 in

Height 5 in
Length 107 in
LengthMetric 271.8 mm
Weight 12 lb
WeightMetric 5.4 kg
Width 5 in

#### **Product Assets**

Catalogs - Insulated Hand Tools (2100)
Installation Manuals - CHANCE® Tools Manuals
(CENT\_LTE\_IOM\_EN\_00158)<LineBreak/>
Sales Drawings - Epoxiglas Gripall (SA4030291)

## **Related Products**

P4032312P - Heavy Duty End Cap for 1-1/4" Epoxiglas Pole

