

Copper Automatic Dead End, #4 SOL Copper, 8A CW Conductor, Clevis Bail.

By FARGO Catalog # GD512

Copper Automatic Dead End, #4 SOL Copper, 8A CW Conductor, Diameter range .19 - .20" (4.9 -5.2 mm), Clevis Bail.



*Representative Image

Features

- Fastest method of deadending Copper and Copperweld® conductor
- Flared mouth of gripping unit permits easy conductor installation
- Four segment jaw is precision machined and automatically adjusts to the contour of the wire
- High strength alloy copper tube for gripping Copperweld® conductors

General

Bail Option Clevis Bail
EU RoHS Indicator Contact Manufacturer

Material Copper: Steel Material - Bail Galvanized Steel Material - Pin (Clevis) Galvanized Steel Material - Pin (Cotter) Stainless Steel Material - Shell Copper Alloy **Product Category** Clevis Bail Type Automatic UPC 096359309291

Dimensions

Length	6.880 in
Weight	0.590 lb
Width	0.780 in

Conductor Related

Conductor Diameter - 0.2 Maximum

Conductor Diameter - 0.19

Minimum

Conductor Diameter Range 0.19 - 0.2

Logistics

Pallet Quantity 3600

Product Assets

Catalogs - Distribution Connectors (CA05127E) Literature - Ropes Course Industry Letter (April 2021) Sales Drawings - CC-24780

