

Copper Automatic Dead End, #3 SOL and #4 STR Copper, 6A CW Conductor, Clevis Bail.

By FARGO Catalog # GD513

Copper Automatic Dead End, #3 SOL and #4 STR Copper, 6A CW Conductor, Diameter range .22 - .23" (5.7- 5.9 mm), Clevis Bail.



*Representative Image

Features

- Fastest method of deadending Copper and Copperweld® conductor
- Flared mouth of gripping unit permits easy conductor installation
- Four segment jaw is precision machined and automatically adjusts to the contour of the wire
- High strength alloy copper tube for gripping Copperweld® conductors

General

UPC

Bail Option Clevis Bail **EU RoHS Indicator** Contact Manufacturer Material Copper: Steel Material - Bail Galvanized Steel Material - Pin (Clevis) Galvanized Steel Material - Pin (Cotter) Stainless Steel Material - Shell Copper Alloy **Product Category** Clevis Bail Type Automatic

Dimensions

Length	6.880 in
Weight	0.550 lb
Width	0.780 in

Conductor Related

Conductor Diameter - Maximum	0.23
Conductor Diameter - Minimum	0.22
Conductor Diameter Range	0.22 - 0.23

Logistics

Pallet Quantity 3200

Product Assets

Catalogs - Distribution Connectors (CA05127E) Literature - Ropes Course Industry Letter (April 2021) Sales Drawings - CC-24780



096359309307