

## Automatic Splice, Full Tension, for 3/8" EHS, AW, AWAC

By ANDERSON  
Catalog # [GLS5042](#)



Automatic Splice, Full Tension, for 3/8" Alumoweld HS,  
Common, Utilities, Siemens-Martin guy grades

\*Representative Image

### Features

- Individually bagged to seal out dirt before use
- GLS Automatic splices will hold a minimum of 90% of the guy wire breaking strength

### General

Catalog Number	GLS5042
Color Code	None
Material	Aluminum Alloy; Steel
Material - Gripping Unit	Plated Steel
UPC	096359389491

### Dimensions

Dimensions	10.000 in x 1.480 in x 1.480 in
Height	1.48 in
Length	10 in
Weight	1.207 lb
Width	1.48 in

### Conductor Related

Conductor Diameter - Maximum	0.372 in
Conductor Diameter - Minimum	0.348 in
Conductor Diameter Range	0.348 - 0.372

### Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
UL Listed	No

### Logistics

Pallet Quantity	1600
-----------------	------

### Product Assets

- [Catalogs - Distribution Connectors](#)
- [Catalogs - Communication Connectors - Deadends and Splices](#)
- [Sales Drawings - GLS5xxx\\_sales\\_drawing](#)
- [Specifications - GLS5042](#)