



NOTES:

1. SWITCH RATED 40,000A MOMENTARY.
2. INSULATOR TO BE INS110BIL OR EQUAL.
3. LIVE PARTS ARE CU, CU ALLOY, OR STAINLESS STEEL.
4. TERMINAL PAD IS TINNED.
5. CONTACTS ARE SILVER TO SILVER.
6. INSULATOR END WITH THE LARGER ROOT DIAMETER MUST BE ORIENTED TOWARD THE MOUNTING SURFACE.
7. REFERENCE ROYAL DRAWING: B17771.

CUSTOMER: HD SUPPLY

ITEM NO.: 19839CHES200.A

S.O. NO.:

CUSTOMER P.O. NO.:

QTY REQ'D:

DATE REQ'D:

# ROYAL SWITCHGEAR MANUFACTURING CO.

3995 PINE LANE S.E., BESSEMER, ALABAMA 35022

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPRIETARY PROPERTY OF ROYAL AND ARE ISSUED ON CONDITION THAT THEY ARE NOT COPIED REPRINTED OR DISCLOSED TO ANY THIRD PARTY, EITHER WHOLLY OR IN PART, WITHOUT THE CONSENT IN WRITING OF ROYAL.

FOR:						MAT: SEE BOM		TITLE: ASSEMBLY OF 15KV 900A TYPE BILT DISCONNECT	
THIS DRAWING SUPERSEDES						FIN: SEE BOM		DRAWN: C.OGLESBY DATE: 08-21-15	
DATED						TOLERANCE UNLESS SPEC'D		CHECKED: <i>[Signature]</i> DATE: 8-21-15	
						1 PLC DEC +/- 0.015"		SCALE: NTS	
						2 PLC DEC +/- 0.010"		ENGINEER: CO	
						3 PLC DEC +/- 0.005"		DATE: 8-21-15	
						FRACTIONS +/- 1/16"		PART DRAWING NUMBER	
						DEGREES +/- 2°		ISSUE	
NO.	DATE	REVISION RECORD	BY	CHK	ENG	B		19839CHES200.A	
								1	

FILE: G:\DRAWINGS\RSWDWGB\B17771-1.DWG