


**- NOTES -**  
 1. ALL FASTENER HARDWARE IS GALVANIZED FOR CORROSION PROTECTION



CAT./PART NUMBER	"L"	ROD LENGTH
1CSM12	12.0	11.33
1CSM15	15.0	14.50
1CSM18	18.0	17.54
1CSM21	21.0	20.64
1CSM24	24.0	23.75
1CSM30	30.0	29.97
1CSM36	36.0	36.19

SECTION A-A

PART OR ASSEMBLY NO:	LATEST EC NO:	REV. <b>A</b>	DATE	CHANGED BY	RESP ENGINEER	INTERNAL MFG COST ESTIMATE NO:	ENG PROJ NO:		
DESCRIPTION OF CHANGES:						AREAS AFFECTED BY LATEST EC: Y N	DO NOT SCALE THIS DWG	THIRD ANGLE PROJECTION	
								CF THIS SYMBOL IDENTIFIES CRITICAL FEATURES	
REASON(S) FOR CHANGE:						DRN BY: ARNONE	DATE: 02-28-11	TITLE: <b>STANDOFF, COMMUNICATIONS</b>	SIZE: <b>B</b>
DISPOSITION OF MAT'L:								CAE CAD CAM	DWG NO: <b>SA1CSM12</b>

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL / A.B. CHANCE COMPANY. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT WRITTEN CONSENT BY HUBBELL / A.B. CHANCE COMPANY. © 2001 HUBBELL/A.B. CHANCE. UNPUBLISHED - ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS