

**GROUNDING CABLE**

- Copper Stranded
- Tough jacket material
- Fine strands for flexibility
- Easy to strip for preparation
- Cable is available in a yellow neoprene jacket or a clear pvc jacket



**13698**



**13701**

CAT NO	SIZE	STRANDS*	WIRE DIAMETER INCHES	OVERALL DIAMETER INCHES	APPROXIMATE WEIGHT PER 1,000 FEET
<b>YELLOW JACKET COPPER GROUND CABLE</b>					
9206	#2	665	.320	.435	263
9201	1/0	1064	.410	.570	414
13698	2/0	1323	.470	.620	504
9228	4/0	2107	.590	.740	775
<b>CLEAR JACKET COPPER GROUND CABLE</b>					
13692	#2	665	.350	.530	300
21263	1/0	1064	.450	.640	475
13701	2/0	1323	.490	.700	565
21264	4/0	2107	.620	.840	856
*NOTE: STRANDS SHOWN ABOVE ARE PER ASTM 855, ALL HASTINGS GROUNDING CABLE IS MANUFACTURED TO ASTM STANDARDS. (STRANDING MAY VARY WITH MANUFACTURER.)					

FAULT CURRENT RATING TABLE FOR GROUNDING CABLE		
GROUND CABLE SIZE AWG	RATINGS IN AMPERES SYMMETRICAL RMS 60 HERTZ	
	15 CYCLES	30 CYCLES
#2	14,500	10,000
1/0	21,000	15,000
2/0	27,000	20,000
4/0	43,000	30,000

C-HEAD GROUND CLAMPS



	CAT NO	DESCRIPTION	CLAMPS WITH 5H RATING*	MAIN LINE RANGE MAXIMUM MINIMUM	MAXIMUM SIZE CABLE	MAXIMUM FAULT CURRENT RATING	TERMINAL TYPE	LBS
BRONZE	21070	SERRATED JAW	*5H RATED	2.88 O.D. CABLE OR BUS 6 SOLID .16" DIA	4/0	43KA@ 15 CYCLES 30KA@ 30 CYCLES	THREADED	3.3
	21552	SERRATED JAW		500 MCM .813 DIA 8 SOLID .128 DIA				1.4
	21307	SERRATED JAW	*5H RATED	1.033 MCM ACSR 1.25 DIA 6 SOLID .16 DIA				2.3
ALUMINUM	21575	SERRATED JAW	*5H RATED	1.50" DIA CABLE OR BUS 6 SOLID .16 DIA	4/0	43KA@ 15 CYCLES 30KA@ 30 CYCLES	THREADED	1.5
	10375	SERRATED JAW	*5H RATED	2" DIA CABLE OR BUS 4 SOLID .18 DIA				1.8
	10376	SAME AS 10375 BUT WITH SMOOTH UPPER JAW						1.8
	11190	SERRATED JAW		1.0335 MCM ACSR 1.5 DIA 8 SOLID .12 DIA			BOLTED	1.3
	11192	SAME AS 11190 BUT WITH SMOOTH UPPER JAW		1.0335 MCM ACSR 1.5 DIA 8 SOLID .12 DIA				1.3
	3172	SMOOTH JAW		2" DIA CABLE OR BUS 6 SOLID .16 DIA				2.4

**5H RATED GROUND SETS (See Above)\***

HASTINGS 5H Rated Ground Sets require all components (Clamps, 4/0 Cable, Ferrules, Etc.) to be manufactured and assembled by HASTINGS.

HASTINGS strictly will not recognize or approve a 5H Rating for any Ground Set(s) that are not manufactured and assembled by HASTINGS.