

## 15 kV, Load Break Elbow w/ Bimetal Contact

By Hubbell Power Systems  
Catalog # [215LE58](#)

Load Break Elbow, 200 Amp, 15 kV, Long Bimetal Contact, Cable Insulation Diameter range = 0.760 - 1.135 inches



### Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, integral seal, cold shrink jacket seal kit or shield adapter kit

### Specifications

EU RoHS Indicator	No
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)

### Conductor

Solid or Compacted Conductor	250
Stranded or Compressed Conductor	4/0

### Configuration

With Seal Kit	No
With Test Point	No
Connector Type	Bi-Metal

### Current

Current Rating	200 A
AC Withstand Voltage (1 min)	34 kV
Corona Extinction (3pC)	11 kV

Basic Impulse Level	95 kV
kV Class	15 kV

### Dimensions

Length	7.50 in
Cable Insulation Diameter Minimum	0.760 in
Cable Insulation Diameter Maximum	1.135 in
Width	2.875 in
Weight	2.750 lb.
Height	9.00 in
Dimensions	7.50 in x 2.875 in x 9.00 in

### General

Material type	Standard
PROBELOK® Connectors	No
Type	200Amp Load Break
UPC	096359500834
Integral Seal	No

### Logistics

Standard Package	20
Pallet Quantity	240

### Product Assets

- [Catalog \[English\]](#)  
[Installation Manual \[English\]](#)