



NOTES:

1. DIMENSIONS SUBJECT TO +/- 3% TOLERANCE
2. LEAKAGE DISTANCE (Inches) - 52.0
3. ALTITUDE 0-12000 FT. ABOVE SEA LEVEL
4. WEIGHT OF UNIT INCLUDING HARDWARE - 4.6 LB.
5. MAXIMUM CONTINUOUS LINE-TO-GROUND OPERATING VOLTAGE 29 KV MCOV
6. VOLTAGE RATING 36 kV RMS.
7. PVR RISER LABEL ON UNDERSIDE OF INSULATING BASE, OR ARRESTER



MAXIMUM DISCHARGE VOLTAGE (kV)								
FOW	SWITCHING SURGE	8/20 LIGHTNING IMPULSE						
		1.5 kA	3.0 kA	5 kA	10 kA	20 kA		
10 kA	500 A	107.4	75.7	81.2	85.5	89.4	96.1	108

RISER POLE SURGE ARRESTER	<p>CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</p>			<p>HUBBELL® POWER SYSTEMS</p>			
		<p>TITLE PVR ARRESTER 29 KV MCOV</p>					
REV DATE	06/22/20	SIZE	DWG NO.	CAT / PART / ASSY NO.	REV		
		S	ALES7XXX	221629-7314	33		
DO NOT SCALE THIS DRAWING		DRN BY PRO		DATE 06/17/00	SHEET 1 OF 1		