

# HUBBELL Power Systems

## 25/28 kV, Load Break Elbow w/ Test Point, Bimetal Contact, Seal Kit

By Hubbell Power Systems  
Catalog # [228LE55TJ](#)

Load Break Elbow, 200 Amp, 25/28 kV, with Test Point, Long Bimetal Contact, Cable Insulation Diameter range = 0.920 - 1.310 inches



### Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, integral seal, cold shrink jacket seal kit or shield adapter kit

### Conductor

Solid or Compacted Conductor 2/0  
Stranded or Compressed 1/0  
Conductor

### Configuration

With Seal Kit Yes  
With Test Point Yes  
Connector Type Bi-Metal

### Current

Current Rating 200 A  
AC Withstand Voltage (1 min) 45 kV  
Corona Extinction (3pC) 21 kV  
Basic Impulse Level 125 kV  
kV Class 25/28 kV

### Dimensions

Cable Insulation Diameter Minimum 0.920 in  
Cable Insulation Diameter Maximum 1.310 in  
Width 2.75 in  
Weight 3.500 lb.  
Height 9.00 in  
Length 7.50 in  
Dimensions 7.50 in x 2.75 in x 9.00 in

### General

Type 200Amp Load Break  
Material type Non-Standard  
PROBELOK® Connectors No  
UPC 096359625698  
Integral Seal No

### Logistics

Standard Package 20  
Pallet Quantity 240

### Product Assets

[Catalog \[English\]](#)  
[Installation Manual \[English\]](#)