

## 35 kV Class Large Interface Elbow Arrester

By Hubbell Power Systems  
Catalog # 236ELA27

Large Interface Elbow Arrester, 35KV 22 MCOV



### Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

### Specifications

EU RoHS Indicator No

### Current

MCOV	22 kV
kV Class	35 kV
Maximum Switching Surge	69.0 kV
Protective Level @ 500A	
Maximum Discharge Voltage	<ul style="list-style-type: none"><li>• 70.8 kV @ 1.5 kA</li><li>• 75.4 kV @ 3 kA</li><li>• 80.4 kV @ 5 kA</li><li>• 90.5 kV @ 10 kA</li><li>• 104.6 kV @ 20 kA</li><li>• 130.7 kV @ 40 kA</li></ul>
Duty Cycle	27 kV

### Dimensions

Weight	6.500 lb.
Height	16.69 in
Width	3.625 in
Length	10.50 in
Dimensions	10.50 in x 3.625 in x 16.69 in

### General

Material type	Standard
UPC	096359684527
Type	Underground Arresters
Grounding Style	36 in Line Lead

### Logistics

Pallet Quantity	64
Standard Package	1

### Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

### Product Assets

[Catalog \[English\]](#)  
[Catalog \[English\]](#)