



Catalog No. 262LR-C5240

Product Details



UPC: 075114192095

Details: 25kV 200 Amp, Loadbreak Elbow Connector with Test Point, .805 inch - 1.060 Inch Cable Insulation Diameter, 1/0 Stranded Wire Size, Bi-Metal Compression Lug.

Product Details

Details

Catalog No.	262LR-C5240
Description	25 LB ELB W/TP 1/0STRN .805-1.060
Std. Package Weight	2.350 LB
Product Family	9CS
Restock Fee	
Customer Reference No.	
Brand Name	ELASTIMOLD
Minimum Order Qty.	1

UPC	075114192095
GSA Compliance	No
Discount Schedule	9C
CCC	
Currency	USD
Notes	
Package Qty.	1
Country Or Territory Of Origin	United States

General Characteristics

Category	Electrical connector assembly
Special Features	28kV, 200 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provision for hot stick operation. Provision for ground wire connection. Wide cable range with minimum number of sizes. Long bi-metal compression lug is standard. Non-corrosive capacitive test point.
Application	200 kV, 200 Amp
Conductor Range	1/0 STR/COMPR AWG , 2/0 SOL/COMPT AWG
Material	Housing - EPDM Rubber
Color	Black
Voltage Rating	28 kV
Amperage Rating	200 A
Insulation	Yes, EPDM Rubber
Temperature Rating	-40 to +65 C
Environmental Conditions	All Weather Conditions

Dimensions and Classifications

Brand Name	Elastimold
Standard	ANSI/IEEE Standard 386
Size	9.03 inch (299.4 mm) X 8.20 inch (208.3 mm) not including probe, 2.86 inch (72.6 mm) Diameter

