



PINPOINT

1 1/2" SDR 13.5



Min. ID	1.578 in
Nominal OD	1.9 in
Min. Wall	0.141 in
Locate Wire (Awg)	18
Weight	0.354 lb/ft
Height	2.145 in
Width	1.9 in
Bend Radius Sup	19 in
Bend Radius UnSup	38 in
Conduit SWPS	1867 lbs



STANDARD DETAILS

SPECIFICATIONS	Wire is 18 AWG copper clad 30.041 ohm/1,000 ft 68°F
INSTALLATION TYPES	Plow, Trench, Directional Bore
COLORS	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Lilac, Pink, Aqua, Terra Cotta, Lime Green, or custom colors with optional stripes
CONDUIT MARKINGS	Permanent marking along conduit includes: material, relevant standards, production info, and sequential feet or meter markings. Custom options available.

OPTIONS

PRE-INSTALLED TAPE	Factory pre-installed Bull-Line™ Pull Tape with EVEN-LOAD™ ensures extra slack at any access point throughout the reel. Available 500lb–6,000lb tensile strength or locatable.
CO-EXTRUDED LINING	SILICORE® ULF (Ultra-Low Friction) is co-extruded inside the HDPE wall creating a slick, permanent, interior lining. With a coefficient of friction 60% lower than standard HDPE conduit without the aid of wet lubricants, SILICORE® ULF exhibits no loss in performance over time or in extreme temperature conditions. Coefficient of friction for SILICORE ULF 0.07 versus non-lubricated HDPE conduit 0.18-0.22 (internal test method).
INTERNAL RIBS	Internal ribs available upon request
UV PROTECTANT	Available for UV exposure applications (Aerial, Lashed, or External Tray)

REEL SPECIFICATIONS

REEL SIZE	STANDARD LENGTH	REEL TYPE
83 x 46 in	3000 ft	Steel
96 x 46 in	5000 ft	Steel

PRODUCT COMPLIANCE

We offer an extensive portfolio of US-made conduit products and accessories that conform with several domestic preference standards, including Buy America (BAA), Build America, Buy America (BABA), and DOT Buy American requirements. Any products including a locate wire or preinstalled cables, will need to be specifically evaluated. Fire Retardant Resins may also require additional evaluation to meet program guidelines. Please contact your Dura-Line representative for more information.



† Safe working pull strength is calculated at 80% of tensile or breaking strength

* Unsupported Bend Radius guidelines should be followed during the installation process. The Supported Bend Radius are post-installation measurements.

PINPOINT RECOMMENDED ACCESSORIES

1 1/2" SDR 13.5

1 1/2" SHUR-LOCK II		1.50" CLEAR-LOCK PINPOINT SPLICE KIT		ROTARY CONDUIT CUTTER 0.75" TO 2.625"	
Quantity: 10 / Per Case Packaging: Case Part Number: 20000122		Quantity: 2 / Per Case Packaging: Case Part Number: 20005753		Quantity: 1 Packaging: Each Part Number: 20001924	
RATCHET CUTTER FOR 0.75" - 1.25" OD CONDUIT		KWIK CUTTER - CUTS UP TO 2.00" OD CONDUIT		CONDUIT SLITTER	
Quantity: 1 Packaging: Each Part Number: 20001923		Quantity: 1 Packaging: Each Part Number: 20001922		Quantity: 1 Packaging: Each Part Number: 20005686	
1.50" SDR FLAT VINYL END CAP 1.875" OD		1.50" SDR TAPERED VINYL END CAP 1.900" OD		1.50" EXPANSION PLUG 1.460" - 1.830" ID	
Quantity: 1 Packaging: Each Part Number: 20002533		Quantity: 1 Packaging: Each Part Number: 20002055		Quantity: 50 / Per Case Packaging: Each Part Number: 20001973	
HYDRALUBE F100I SUMMER (12) 1 QUART		HYDRALUBE F150I SUMMER (4) 1 GALLON		PINPOINT WIRE CONNECTOR 22-16AWG	
Quantity: 24 / Per Pallet Packaging: (12) 1 Quart Part Number: 20000209		Quantity: 30 / Per Pallet Packaging: (4) 1 Gallon Part Number: 20000211		Quantity: 30 / Per Case Packaging: Case Part Number: 20005541	
BULL-LINE POLYESTER TAPE WP12 3000FT		BULL-LINE POLYESTER TAPE WP18 3000FT		BULL-LINE POLYESTER TAPE WP25 3000FT	
Quantity: 48 Packaging: 45" x 45" Part Number: 20000052		Quantity: 36 Packaging: 45" x 45" Part Number: 20000068		Quantity: 36 Packaging: 45" x 45" Part Number: 20000077	
BULL-LINE LOCATABLE TAPE WP12LC 3000FT		BULL-LINE LOCATABLE TAPE WP18LC 3000FT		BULL-LINE LOCATABLE TAPE WP25LC 3000FT	
Quantity: 36 Packaging: 45" x 45" Part Number: 20000059		Quantity: 36 Packaging: 45" x 45" Part Number: 20000163		Quantity: 18 Packaging: 45" x 45" Part Number: 20000155	

† Safe working pull strength is calculated at 80% of tensile or breaking strength

* Unsupported Bend Radius guidelines should be followed during the installation process. The Supported Bend Radius are post-installation measurements.

BULL-LINE ARAMID TAPE WK25 1000FT

Quantity: 100

Packaging: 45" x 45"

Part Number: 20000038



† Safe working pull strength is calculated at 80% of tensile or breaking strength
* Unsupported Bend Radius guidelines should be followed during the installation process. The Supported Bend Radius are post-installation measurements.