



# SMOOTHWALL

2" SCH 40



Nominal OD	2.375 in
OD Tolerance +/-	0.012 in
Min. Wall	0.154 in
Wall Tolerance +	0.02 in
Min. ID	2.027 in
Avg ID	2.047 in
Weight	0.469 lb/ft
Bend Radius Sup	24 in
Bend Radius UnSup	48 in
Conduit SWPS	2579 lbs

## STANDARD DETAILS

<b>DETAILS</b>	Manufactured from flexible HDPE (High Density Polyethylene)
<b>SPECIFICATIONS</b>	All Smoothwall conduit dimensions meet or exceed one or more of the following: ASTM F-2160, ASTM D-3350, ASTM D-3485, NEMA TC-7, UL 651A, UL 1990, Bellcore GR-356, CSA C22.2 No. 327-18
<b>INSTALLATION TYPES</b>	Plow, Trench, Directional Bore, Direct Burial, Tray Installations, Subdivided Conduit, Aerial
<b>COLORS</b>	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Lilac, Pink, Aqua, Terra Cotta, Lime Green, or custom colors with optional stripes
<b>CONDUIT MARKINGS</b>	Permanent marking along conduit includes: material, relevant standards, production info, and sequential feet or meter markings. Custom options available.

## OPTIONS

<b>CO-EXTRUDED LINING</b>	SILICORE® ULF (Ultra-Low Friction) is co-extruded inside the HDPE wall creating a slick, permanent, interior lining. With a coefficient of friction 60% lower than standard HDPE conduit without the aid of wet lubricants, SILICORE® ULF exhibits no loss in performance over time or in extreme temperature conditions.
<b>PRE-INSTALLED TAPE</b>	Factory pre-installed Bull-Line™ Pull Tape with EVEN-LOAD™ ensures extra slack at any access point throughout the reel. Available 500lb–6,000lb tensile strength or locatable.
<b>PRE-INSTALLED CABLE</b>	Cable can be factory pre-installed in conduit
<b>UV PROTECTANT</b>	Available for UV exposure applications (Aerial, Lashed, or External Tray)

## REEL SPECIFICATIONS

REEL SIZE	STANDARD LENGTH	REEL TYPE
66 x 46 in	1000 ft	Steel
83 x 46 in	2000 ft	Steel
102 x 46 in	4000 ft	Steel

## PRODUCT COMPLIANCE

We offer an extensive portfolio of US-made conduit products and accessories that conform with several domestic preference standards, including Buy America (BAA), Build America, Buy America (BABA), and DOT Buy American requirements. Any products including a locate wire or preinstalled cables, will need to be specifically evaluated. Fire Retardant Resins may also require additional evaluation to meet program guidelines. Please contact your Dura-Line representative for more information.



† Safe working pull strength is calculated at 80% of tensile or breaking strength

\* Unsupported Bend Radius guidelines should be followed during the installation process. The Supported Bend Radius are post-installation measurements.

## SMOOTHWALL RECOMMENDED ACCESSORIES

2" SCH 40

2" SHUR-LOCK II		2" CLEAR-LOCK		2" REDI-LOCK	
<p><b>Quantity:</b> 10</p> <p><b>Packaging:</b> Case</p> <p><b>Part Number:</b> 20000123</p>		<p><b>Quantity:</b> 15</p> <p><b>Packaging:</b> Each</p> <p><b>Part Number:</b> 20005097</p>		<p><b>Quantity:</b> 10</p> <p><b>Packaging:</b> Case</p> <p><b>Part Number:</b> 20005477</p>	
ROTARY CONDUIT CUTTER 0.75" TO 2.625"		RATCHET CUTTER FOR 2.00" OD CONDUIT		CONDUIT SLITTER	
<p><b>Quantity:</b> 1</p> <p><b>Packaging:</b> Each</p> <p><b>Part Number:</b> 20001924</p>		<p><b>Quantity:</b> 1</p> <p><b>Packaging:</b> Each</p> <p><b>Part Number:</b> 20001803</p>		<p><b>Quantity:</b> 1</p> <p><b>Packaging:</b> Each</p> <p><b>Part Number:</b> 20005686</p>	
2.00" SDR FLAT VINYL END CAP 2.375" OD		2.00" SDR TAPERED VINYL END CAP 2.375" OD		2.00" EXPANSION PLUG 1.834" - 2.386" ID	
<p><b>Quantity:</b> 1</p> <p><b>Packaging:</b> Each</p> <p><b>Part Number:</b> 20001815</p>		<p><b>Quantity:</b> 1</p> <p><b>Packaging:</b> Each</p> <p><b>Part Number:</b> 20001740</p>		<p><b>Quantity:</b> 50</p> <p><b>Packaging:</b> Each</p> <p><b>Part Number:</b> 20001870</p>	
HYDRALUBE F150I SUMMER (4) 1 GALLON		HYDRALUBE F200I SUMMER (4) 1 GALLON			
<p><b>Quantity:</b> 30 / Per Pallet</p> <p><b>Packaging:</b> (4) 1 Gallon</p> <p><b>Part Number:</b> 20000211</p>		<p><b>Quantity:</b> 30 / Per Pallet</p> <p><b>Packaging:</b> (4) 1 Gallon</p> <p><b>Part Number:</b> 20000218</p>			

† Safe working pull strength is calculated at 80% of tensile or breaking strength

\* Unsupported Bend Radius guidelines should be followed during the installation process. The Supported Bend Radius are post-installation measurements.