

Catalog No. 15PCJ1F1210



Representative Image

Description: 15KV PWR CBLE JNT1 No3 No2 AL .64

UPC No 783786639069

Home > Medium Voltage Utility Solutions > Elastimold > Cable joint

15kV Power Cable Joint Style 1 with Single Piece Housing, Cable Insulation Diameter 0.640 inch to 0.820 inch. Aluminum Conductor. Conductor Size AWG Stranded #3/Solid #2.

Descriptors

Category	Cable joint
Special Features	Power Cable Joints utilize permanently crimped connectors. PCJ housings are fully insulated, shielded and sealed for direct-burial, vault, submersible and other severe service applications. Units have been designed and tested per IEEE Standard 404 to ensure system matched performance and ratings equal to the cable to which the splice will be installed. Power Cable Joints are available in two styles. Style 1 uses a single-piece housing that is sized to accommodate a specific range of cable - ideally suited to straight splicing of the same or similar cable. Style 2 designs incorporate a universal housing with separate cable adapters to allow transition splices of different types and sizes of cable.
Application	For Direct Burial, Vault, Submersible and Other Severe Service Applications.

Specifications

Connection	Compression
Conductor Range	#3 STR AWG , #2 SOL AWG
Number Of Conductors	2
Material	EPDM Rubber
Color	Black
Voltage Rating	15 kV
Insulation	yes

Classifications

Brand Name	ELASTIMOLD
Standard	IEEE Standard 404

Dimensions

Size	14-3/8 inch long
------	------------------

by ABB