

Catalog No. 25PCJ1H1240

Description: 25KV PWR CABLE JNT1 1/0 2/0 AL .85

UPC No 783786663392

Home > Medium Voltage Utility Solutions > Elastimold > Cable joint

25kV Power Cable Joint Style 1 with Single Piece Housing, Cable Insulation Diameter 0.850 inch to 1.050 inch. Aluminum Conductor. Conductor Size AWG Stranded 1/0 /Solid 2/0.



Descriptors

Category	Cable joint
Special Features	Power Cable Joints utilize permanently crimped connectors. PCJ housings are fully insulated, shielded and sealed for direct-burial, vault, submersible and other severe service applications. Units have been designed and tested per IEEE Standard 404 to ensure system matched performance and ratings equal to the cable to which the splice will be installed. Power Cable Joints are available in two styles. Style 1 uses a single-piece housing that is sized to accommodate a specific range of cable - ideally suited to straight splicing of the same or similar cable. Style 2 designs incorporate a universal housing with separate cable adapters to allow transition splices of different types and sizes of cable.
Application	For Direct Burial, Vault, Submersible and Other Severe Service Applications.

Specifications

Connection	Compression
Conductor Range	1/0 STR AWG , 2/0 SOL AWG
Number Of Conductors	2
Material	EPDM Rubber
Color	Black
Voltage Rating	25 kV
Insulation	yes

Classifications

Brand Name	ELASTIMOLD
Standard	IEEE Standard 404

Dimensions

Size	14-3/8 inch long
------	------------------