



CATALOG NO.	"L"	"T"
29978	8.0	4.0
29980	10.0	4.0
29982	12.0	6.0
29984	14.0	6.0
29986	16.0	6.0
29988	18.0	6.0
29990	20.0	6.0
2999022	22.0	6.0
2999024	24.0	6.0
2999026	26.0	6.0

-NOTES-

1. MATERIAL: STEEL.
2. FINISH: HOT DIP GALVANIZED PER ASTM A153.
3. BOLT AND NUT ASSEMBLY MEETS THE MINIMUM TENSILE LOAD OF 20,050 LBS. PER ANSI C135.4 AND C135.5 (LATEST REVISION).

	HUBBELL POWER SYSTEMS, INC.			
	TITLE OVALEYE BOLT, 3/4"			
CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.	SIZE B	CAT / PART / ASSY NO. SEE CHART	DWG NO. SA29978	REV C
	DO NOT SCALE THIS DRAWING	DRN BY OJS	DATE 5/13/2020	SHEET 1 OF 1