


CATALOG NUMBER	"A"	"B"	"C"
8634	4	3	0.81
400-012-514	4	FULL	0.81
863412	4-1/2	3	0.81
8635	5	3	0.81
400-012-530	6	2	0.81
8636	6	3	0.81
8637	7	3	0.81
400-012-548	8	4	0.81
400-012-555	10	4	0.81
400-012-563	12	4	0.81
400-012-571	14	4	0.81

==NOTES==

1. MATERIAL: STEEL, HOT DIP GALVANIZE PER ASTM A153 (LATEST REV).
2. BOLT AND NUT ASSEMBLY MEETS THE ANSI MINIMUM TENSILE LOAD OF 4,250 LBS AND THE 180° BEND TEST.

CHANCE TOLERANCE CHART		 HUBBELL POWER SYSTEMS <small>POWER SYSTEMS, INC.</small>	
<small>CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</small>		<small>TITLE</small> 3/8" CARRIAGE BOLT	
		<small>SIZE</small> SB SA8634	<small>CAT / PART / ASSY NO.</small> SEE CHART
<small>DO NOT SCALE THIS DRAWING</small>	<small>DRN BY</small> BERGER	<small>DATE</small> 10/18/12	<small>SHEET</small> 01 OF 01