

Compression Splice Conventional (Hex Die) Jumper Loop-Minimum Tension

By FARGO
Catalog # 40117



*Representative Image

"Conventional (Two Die) Compression Jumper Loop Splice available for ACSR and AAC conductor. Loop Splice is Minimum Tension connector (no steel component required)."

Features

- "SAC Diameter Range: 1.014"-1.108"
- COMP/TW Diameter Range: 0.927"-1.010"
- PC suffix denotes prefilled Joint Compound
- Material: Extruded Aluminum Tube.
- Die Size: 30AH 60 Ton Press Min."

General

Aluminum Die	30AH
Catalog Number	40117
Compression Method	Conventional
EU RoHS Indicator	No
Inhibitor Loaded	No
Material	Aluminum Alloy
Press Minimum	60 to
Tension Range	0 lb
UPC	096359250678

Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	9.7 in
Messenger Diameter Range	0 - 0
Weight	1.793 lb

Electrical Ratings

Voltage Application	EHV; Standard
---------------------	---------------

Conductor Related

Conductor Compatibility	ACSR-Cuckoo-795-24/7;ACSR-Drake-795-26/7;ACSR-Condor-795-54/7;AAC-Cockscomb-900-37;AAC-Snapdragon-900-61
Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Diameter (Main) Range	0 - 0
Conductor Diameter - Maximum	1.108 in
Conductor Diameter - Minimum	1.092 in
Conductor Diameter Range	1.092 - 1.108
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
UL Listed	No

Product Assets

[Catalogs - Transmission Connectors Catalog - Full Specifications - 40117](#)