

## Compression Splice Conventional (Hex Die) Jumper Loop-Minimum Tension

By FARGO  
Catalog # 40800



\*Representative Image

"Conventional (Two Die) Compression Jumper Loop Splice available for ACSR and AAC conductor. Loop Splice is Minimum Tension connector (no steel component required)."

### Features

- "SAC Diameter Range: 0.701"-0.752"
- COMP/TW Diameter Range: 0.660"-0.963"
- PC suffix denotes prefilled Joint Compound
- Material: Extruded Aluminum Tube.
- Die Size: 20AH 12 Ton Press Min."

### General

Aluminum Die	20AH
Catalog Number	40800
Compression Method	Conventional
EU RoHS Indicator	No
Inhibitor Loaded	No
Material	Aluminum Alloy
Press Minimum	12 to
Tension Range	0 lb
UPC	096359494645

### Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	6.8 in
Messenger Diameter Range	0 - 0
Weight	0.49 lb

### Electrical Ratings

Voltage Application Standard

### Conductor Related

Conductor Compatibility	ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;AAC-Canna-397.5-19
Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Diameter (Main) Range	0 - 0
Conductor Diameter - Maximum	0.743 in
Conductor Diameter - Minimum	0.72 in
Conductor Diameter Range	0.72 - 0.743
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

### Certifications And Compliance

Buy American Compliant	Contact Manufacturer
UL Listed	No

### Product Assets

[Catalogs - Transmission Connectors Catalog - Full Specifications - 40800](#)