



Southern Pipe	Trade	T Min	OD	ID	E	B	D Min	L
Part Number	Size	Wall Thickness	Outside Diameter	Inside Diameter	Bell Entrance ID	Bell Bottom ID	Bell Depth	Total Length
41505	1/2"	0.109	0.840	0.578	0.852	0.835	1.500	120
41508	3/4"	0.113	1.050	0.780	1.064	1.046	1.500	120
41510	1"	0.133	1.315	1.004	1.330	1.310	1.750	120
41512	1 1/4"	0.140	1.660	1.335	1.677	1.655	2.000	120
41515	1 1/2"	0.145	1.900	1.564	1.918	1.894	2.125	120
41520	2"	0.154	2.375	2.021	2.393	2.369	2.500	120
41525	2 1/2"	0.203	2.875	2.414	2.890	2.868	3.000	120
41530	3"	0.216	3.500	3.008	3.515	3.492	3.625	120
41535	3 1/2"	0.226	4.000	3.486	4.015	3.992	3.875	120
41540	4"	0.237	4.500	3.961	4.515	4.491	4.125	120
41550	5"	0.258	5.563	4.975	5.593	5.553	4.750	120
41560	6"	0.280	6.625	5.986	6.658	6.614	5.750	120
41580*	8"	0.322	8.625	7.853	8.670	8.610	6.750	120

*8" is Non UL-Listed

 Listed 651
 NEMA TC 2
 Sunlight Resistant
 See NEC Article 352 for Usage

RUS Listed
 NEMA TC 18
 90° C Wire



Schedule 40 Rigid Non-Metallic PVC Conduit - 10'

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES
 ALL Dimensions are Nominal

NAME		DATE
DRAWN	K. Mitchell	04/01/13
CHECKED		
ENG APPR		
FILE: SCH 40 10 FOOT.dft		REV 10