

Alternate Catalog No. SA 1/0-48 Catalog No. SA1/0-48

Description: AL 1HOLE LUG STR DIE 1/0

UPC No 783786749607

Home > Connectivity & Grounding > Homac > Wire connectors

Aluminum Compression One-Hole NEMA Lug - Wire Range 1/0 Stranded - Compressed - ACSR, 2/0 Compact. Installing Dies TU, 52, BG, 243, 5/8, CSA22. Length 3-1/8 inch. Pad 57/64 inch wide x 1-5/16 inch x 7/32 inch thick. (1) 9/16 inch Diameter Hole. Barrel 1-3/8 inch. Oxide Inhibitor. Yellow Cap. For use with 1/2 inch bolts. Dual Rated for Aluminum and Copper Conductors

Representative Image

Descriptors

Category	Wire connectors
Special Features	Entire conductor range installed by four dies. Lessens your die inventory. Dual-Rated for use with Aluminum and Copper Conductors. Made of Aluminum for high strength and high conductivity. Prefilled with Oxide Inhibitor to Prevent Oxidation and keep out Moisture. Marked with Conductor Sizes and Die References for Easy Identification.
Application	Designed for general applications and for installation on Homac 125 series insulated buses.

Specifications

Connection	Compression
Material	Aluminum

Classifications

Brand Name	Homac
Standard	ANSI C119.4 ANSI C119.4

Dimensions

Size	3-1/8 x 7/8 inch wide
Wire Size	1/0 STR/COMPR AWG , 2/0 COMPT AWG , 1/0 SOL AWG

Compliance and Certifications

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant

by ABB