

Rigid PVC Conduit & Fittings

- Commercial, Industrial and Utility Usage
- Corrosion Resistant
- Non-Magnetic and non-galvanic
- Self Extinguishing
- Impact Resistant

FEATURES & SPECIFICATIONS

Allied Tube & Conduit offers a complete line of rigid PVC conduit and fittings and PVC utility duct. For commercial, industrial and utility usage, Allied PVC conduit and duct is proven durable and effective for years of maintenance-free performance in underground, encased and exposed applications in accordance with the National Electrical Code.

Corrosion Proof:

Resistant to most chemicals, PVC is typically not affected by corrosive soils or salts.

Non-Magnetic and Non-Galvanic:

Properties of Allied PVC Conduit provide good insulation and no power loss or conductor heating.

Self Extinguishing:

Properties make PVC fire resistant.

Impact Resistant:

Tough, durable, with high tensile strength, yet easy to handle and install right on the jobsite.

Schedule 40 & 80 rigid PVC conduit systems are sunlight resistant and are used exposed, encased in concrete, concealed in walls and in direct burial applications including systems for:

- Utilities
- Cable, data and communication lines
- Institutional, commercial, industrial buildings
- Residential applications, & service entrances
- Street and highway underground feeds
- Transportation systems - subways, bridges, tunnels, airports
- Water and wastewater treatment plants
- Marinas
- Mines and mills

Type DB-60 and DB-120 utility duct are designed for direct burial applications. **Type EB-20 and EB-35** are designed for burial encased in concrete.

Project Information

Company Name: _____

Address: _____

City: _____

State & Zip: _____

Phone: _____

Project Name: _____

City: _____

State: _____



Codes And Standards Compliance

Allied Schedule 40 and Schedule 80 rigid conduits are third-party certified to UL 651 and are allowed for use with 90° C conductors, in accordance with the National Electrical Code. They are manufactured in accordance with NEMA TC2.

Allied Type DB and EB ducts are manufactured in accordance with NEMA TC 6&8 and are allowed for use with 90° C conductors.

Allied PVC fittings are manufactured in accordance with NEMA TC3. The UL standard for PVC fittings is UL 651; for boxes UL 514C, for cover plates UL 514D and for enclosures UL 50.

See product pages for UL listing information.

Specification

All wiring shall be installed in Allied Tube & Conduit rigid PVC conduit and secured by means of proper fittings. All fittings shall be offered by Allied Tube & Conduit. All outlets, pull boxes and junction points shall be fitted with Allied outlet boxes, fittings and junction boxes.

Exposed conduit shall be securely attached and supported by means of straps. The straps shall be installed at the recommended spacing as specified in the National Electrical Code (NEC). The straps must allow for linear expansion and contraction of the conduit due to temperature change. If the variance in temperature exceeds 25°F, expansion joints shall be installed according to the manufacturer's recommendations.


If rigid PVC conduit is embedded in concrete or direct buried, support straps are not required.

PVC Adapters, Straps, & Meter Accessories

Terminal Adapters



Trade Size	Part Number	Unit Quantity	A (in)	B (in)	Inside (ID) Diameter (in)	Length (L) (in)
1/2	59615	200	0.750	0.700	0.591	1.550
3/4	59616	125	1.000	0.675	0.790	1.750
1	59617	70	1.115	0.625	1.000	1.860
1-1/4	59618	40	1.300	0.640	1.311	2.125
1-1/2	59619	30	1.425	0.725	1.530	2.250
2	59620	40	1.150	0.800	1.970	2.100
2-1/2	59621	20	1.900	0.800	2.346	2.930
3	59622	40	2.000	0.815	2.915	3.055
3-1/2	59623	30	1.715	1.000	3.385	3.055
4	59624	20	1.990	0.815	3.850	3.215
5	59625	10	2.000	1.725	5.015	5.985
6	59626	8	2.130	1.875	6.025	6.500

Listed to UL651



Female Adapters - NPT Tapered Thread

Trade Size	Part Number	Unit Quantity	A (in)	B (in)	Inside (ID) Diameter (in)	Length (L) (in)
1/2	59630	200	0.800	0.825	0.620	1.725
3/4	59631	125	0.800	1.000	0.820	1.900
1	59632	70	1.000	1.200	1.065	2.300
1-1/4	59633	40	1.015	1.300	1.395	2.425
1-1/2	59634	30	1.050	1.290	1.575	2.440
2	59635	40	1.075	1.375	2.050	2.550
2-1/2	59636	20	1.675	1.985	2.470	3.760
3	59637	40	1.630	2.150	3.090	4.100
3-1/2	59638	30	1.800	2.000	3.540	3.985
4	59639	20	1.755	2.185	4.025	4.210
5	59640	10	2.065	3.000	5.035	5.240
6	59641	8	2.065	3.000	6.045	5.235



Meter Hubs

Trade Size	Part Number	Unit Quantity
1-1/4	802801	50
1-1/2	802802	25
2	802803	50

Listed to UL651



Meter Offsets

Trade Size	Part Number	Unit Quantity
1-1/4	59193	15
2	59194	8

Listed to UL651



Service Entrance Fittings

Trade Size	Part Number	Unit Quantity
1/2	59269	10
3/4	59270	10
1	59271	20
1-1/4	59272	20
1-1/2	59273	20
2	59274	5
2-1/2*	59275	5
3	59276	5
3-1/2*	59277	5
4	59278	1

Listed to UL651



Pipe Straps* - PVC - 2 Hole

Trade Size	Part Number	Unit Quantity
1/2	59280	300
3/4	59281	200
1	59282	200
1-1/4	59283	200
1-1/2	59284	200
2	59285	200

Listed to UL651



Pulling Elbow

Trade Size	Part Number	Unit Quantity
1/2	52400	75
3/4	52401	50

Listed to UL651



PVC Conduit & Fittings are not available in all markets.

Please contact your Allied representative or distributor for details.

16100 S. Lathrop Ave., Harvey, IL 60426

Phone / 708.339.1610 • Toll-Free / 800.882.5543

NOTE: Special orders are non-cancelable, non-returnable and non-refundable

www.alliedeg.com