

**25/28 kV, 600 Amp, T-Body Kit w/  
Test Point**

By Hubbell Power Systems  
Catalog # [625BTL27T](#)

25/28 kV 600 Amp T-Body Kit with Test Point. Cable insulation range 1.180 in - 1.465 in. Kit includes T-body, insulating plug with cap, 4/0 compression lug, threaded stud, and cable adapter

**Features**

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, shear bolt connector, cold shrink jacket seal kit or shield adapter kit

**General**

Catalog Number	625BTL27T
Connector Type	Aluminum
EU RoHS Indicator	No
Type	600 Amp Dead Break
UPC	096359391937
With Seal Kit	No
With Test Point	Yes

**Dimensions**

Weight	8.15 lb
--------	---------

**Electrical Ratings**

AC Withstand Voltage (1 min)	45 kV
Basic Impulse Level	125 kV
Corona Extinction (3pC)	21 kV
Current Rating	600 A



\*Representative Image

kV Class	25/28 kV
----------	----------

**Conductor Related**

Solid or Compacted Conductor	250
Stranded or Compressed Conductor	4/0

**Certifications And Compliance**

Buy America(n) Qualified	Contact Manufacturer
--------------------------	----------------------

**Logistics**

Pallet Quantity	64
Standard Package	1

**Product Assets**

- [Catalogs - Cable Accessories](#)
- [Installation Manuals - Deadbreak Connector 600A, 15/25kV Class T-Body](#)
- [Sales Drawings - 25/28 kV Deadbreak Elbow Kit](#)
- [SDS - VERSILUBE G661 SILICONE COMPOUND](#)
- [Specifications - 625BTL27T](#)
- [Test Documents - Cable Accessories Test Report - 15kV & 25kV 600A](#)
- [Video - Hubbell Power Systems In Depth: Proper Torque for Underground Cable Accessories](#)
- [Video - Hubbell Power Systems T-Body Connector Assembly](#)
- [Video - Hubbell Power Systems In Depth: T-Body Kits](#)