

## TapMaster Junction, Mounting U-Straps, 3 positions

By Hubbell Power Systems  
Catalog # [628TM626U](#)



TapMaster Junction 3-PT U-STRAPS 25KV

### Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

### General

Catalog Number	628TM626U
EU RoHS Indicator	No
Mounting Type	U-Straps
Number of Positions	3
Type	600 Amp Dead Break
UPC	096359656999

### Dimensions

Weight	20.3 lb
--------	---------

### Electrical Ratings

AC Withstand Voltage (1 min)	45 kV
Basic Impulse Level	125 kV

Corona Extinction (3pC)	21 kV
Current Rating	600 A
kV Class	15 kV;25/28 kV

### Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	---

### Logistics

Standard Package	1
------------------	---

### Product Assets

- [Catalogs - Cable Accessories](#)
- [Sales Drawings - 628TM626U Drawing](#)
- [SDS - VERSILUBE G661 SILICONE COMPOUND](#)
- [Specifications - 628TM626U](#)
- [Test Documents - Cable Accessories Test Report - 15kV & 25kV 600A](#)
- [Video - Hubbell Power Systems In Depth: Proper Torque for Underground Cable Accessories](#)
- [Video - Grease Best PRactices](#)