



DRY ARCING DISTANCE _____ 188 MM (7.4 IN)
 LEAKAGE DISTANCE _____ 279 MM (11.0 IN)
 60 Hz DRY FLASHOVER _____ 90 kV
 60 Hz WET FLASHOVER _____ 70 kV
 IMPULSE POS. CRITICAL FLASHOVER _____ 150 kV
 IMPULSE POS. WITHSTAND _____ 140 kV
 SCL _____ 12.5 kN (2800 LB)
 RCL _____ 5.5 kN (1235 LB)
 NET WEIGHT _____ 4.5 KG (9.9 LB.)

HUBBELL/BRASS
TOLERANCE CHART

CONFIDENTIAL: THIS DRAWING AND ITS
 CONTENTS ARE CONFIDENTIAL AND THE
 EXCLUSIVE PROPERTY OF HUBBELL
 POWER SYSTEMS. NO PUBLICATION,
 DISTRIBUTION OR COPIES MAY BE MADE
 WITHOUT THE WRITTEN CONSENT OF
 HUBBELL POWER SYSTEMS.
 HUBBELL POWER SYSTEMS UNPUBLISHED
 ALL RIGHTS RESERVED UNDER THE
 COPYRIGHT LAWS.



HUBBELL® POWER SYSTEMS

TITLE
VERI LITE
15 KV LINE POST

SIZE S	DWG NO. --	CAT / PART / ASSY NO. 80S015-0100	REV 2
-----------	---------------	--------------------------------------	----------

REV DATE 08/21/07	DO NOT SCALE THIS DRAWING	DRN BY JVR	DATE 08/31/05	SHEET 1 OF 1
----------------------	------------------------------	------------	---------------	--------------