

Veri\*Lite Line Post Insulator SR 15  
kV

By OHIO BRASS  
Catalog # 80S0150100



Horizontal Line Post 15 kV Clamptop / Gain Base.

Features

- Weathersheds molded with proprietary silicone rubber
- Proven direct bond interface

Application

Horizontal Line Post

General

Cantilever Bending Strength - Max.	2800 Lbs (12.5 kN)
Cantilever Bending Strength - Routine	1235 Lbs. (5.5 kN)
Catalog Number	80S0150100
EU RoHS Indicator	Contact Manufacturer
Fitting - Ground/Base	Gain Base
Fitting - Live Line End	Horizontal Clamptop
Material	Silicone
Material - End Fitting	Galvanized Steel
Number of Sheds	2
Tension Range	2500 lb
UPC	096359438434

Dimensions

Angle	5
Diameter - Shed(s)	4.8" (121mm)
Dimensions	15 in x 4.77 in x 12 in
Height	12 in
Length	15 in
Length - Effective	12.5 in
Rod Diameter	1.5 in

Thickness - Housing	0.22" (5.5mm)
Weight	9.8 lb
Width	4.77 in

Electrical Ratings

Arc Distance - Dry	7.4" (188mm)
Creep and Leakage Distance	11.0" (279mm)
Critical Impulse Flashover (CIFO) - Positive	150 kV
Flashover Voltage - 60 Hz Dry	90 kV
Flashover Voltage - 60 Hz Wet	70 kV
Voltage - Line	15000 V
Voltage Rating	15 kV
Withstand Voltage - Lightning Impulse (Positive)	140 kV

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Industry Standard(s)	ANSI

Logistics

Carton Quantity	2
Pallet Quantity	40
Standard Package	3

Product Assets

[Catalogs - Veri\\*Lite Line Post Insulators Catalog](#)  
[Literature - Silicone Insulators](#)  
[Sales Drawings - Veri Lite 15 KV Line Post \(Reference Only\)](#)  
[Specifications - 80S0150100](#)