

Veri*Lite Line Post Insulator SR 15 kV

By OHIO BRASS
Catalog # [80S0150K09](#)

Line Post 15 kV Universal Clamp / Stud Base 3/4"-10 Tap.



*Representative Image

Features

- Weathersheds molded with proprietary silicone rubber
- Proven direct bond interface

Application

Universal Clamp

General

Cantilever Bending Strength - Max.	2801 Lbs (12.5 kN)
Cantilever Bending Strength - Routine	1236 Lbs. (5.5 kN)
Fitting - Ground/Base	3/4" Stud Base
Fitting - Live Line End	Universal Clamp Al
Material	Silicone
Material - End Fitting	Aluminum
Number of Sheds	3
Tension Range	2500 lb
UPC	096359665991

Dimensions

Angle	0
Diameter - Shed(s)	4.8" (121mm)
Length - Effective	13.0 in
Rod Diameter	1.5 in
Thickness - Housing	0.22" (5.5mm)
Weight	6.9 lb

Electrical Ratings

Arc Distance - Dry	7.4" (188mm)
Creep and Leakage Distance	11.0" (279mm)
Critical Impulse Flashover (CIFO) - Positive	150 kV
Flashover Voltage - 60 Hz Dry	90 kV
Flashover Voltage - 60 Hz Wet	70 kV
Voltage - Line	15000 V
Voltage Rating	15 kV
Withstand Voltage - Lightning Impulse (Positive)	140 kV

Certifications and Compliance

Industry Standard(s)	ANSI
----------------------	------

Logistics

Carton Quantity	3
Pallet Quantity	60
Standard Package	4

Product Assets

[Catalogs - Veri*Lite Line Post Insulators Catalog \(CA08051E\)](#)
[Sales Drawings - Veri Lite 15 kV Line Post \(80S015-OK09\) \(Reference Only\)](#)