



-NOTES-

1. BOLTS/NUTS MEET ANSI B18.2.1/B18.2.2 RESPECTIVELY.
2. HOT DIP GALVANIZED PER ASTM A153.
3. NUTS TAPPED AFTER GALVANIZING.
4. ALL DIM'S. BEFORE GALVANIZING.



CATALOG NUMBER	NOMINAL DIAMETER	THREAD	DESCRIPTION	"A"	"B"
8604	3/8"	3/8-16UNC-2A	3/8" X 4" MACHINE BOLT	4.00	3.0
8604-1/2	3/8"	3/8-16UNC-2A	3/8" X 4.5" MACHINE BOLT	4.50	3.0
8605	3/8"	3/8-16UNC-2A	3/8" X 5" MACHINE BOLT	5.00	3.0
8605-1/2	3/8"	3/8-16UNC-2A	3/8" X 5.5" MACHINE BOLT	5.50	3.0
T206-0412	3/8"	3/8-16UNC-2A	3/8" X 6" MACHINE BOLT	6.00	3.0

CHANCE TOLERANCE CHART		 HUBBELL® POWER SYSTEMS <small>POWER SYSTEMS, INC.</small>	
<small>CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</small>		TITLE BOLTS, MACHINE 3/8"	
SIZE	DWG NO.	CAT / PART / ASSY NO.	REV
SB	SA8604	SEE CHART	B
DO NOT SCALE THIS DRAWING	DRN BY WILSON	DATE 01/03/13	SHEET 1 OF 1