

Compression Splice Uni-Grip®(One Die) Full Tension

By FARGO
Catalog # [A151351](#)

A full-tension compression splice assebmly for ACSR conductor consists of a prefilled aluminum body and two core wire gripping units.

Features

- For use with 954.0 kcmil 54/7 ACSR code name Cardinal
- Full tension splice assembly
- Outside Diameter is 1.196 inches
- One Die Compression with die size 13CD
- Material: Body – seamless extruded aluminum alloy tube, Gripping Unit – aluminum alloy
- Splices are prefilled with inhibitor and barrel ends plugged.
- For Extra Length repair splice Add "XL" suffix and repair cutoff length in Inches. Example: A151128XL24
- Splices are EHV rated where conductor dia. is 1" or larger.

General

Catalog Number	A151351
Compression Method	Uni-Grip (single die system)
Die Size	13CD
EU RoHS Indicator	No
Material	Aluminum Alloy
Press Minimum	60 to
Tension Range	0 lb
UPC	096359277866

Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Diameter - Outside	1.196 in
Insulator / Conductor Hole Spacing	0 in



*Representative Image

Length Before Compression	23.4 in
Messenger Diameter Range	0 - 0
Weight	4.704 lb

Electrical Ratings

Voltage Application	EHV; Standard
---------------------	---------------

Conductor Related

Conductor Compatibility	ACSR-Cardinal-954-54/7
Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Diameter (Main) Range	0 - 0
Conductor Type	ACSR
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
UL Listed	No

Product Assets

[Catalogs - Transmission Connectors Catalog - Full Specifications - A151351](#)