



### Account Details

Account No. 9036149\_USS6\_10\_10  
 Account KENTUCKY ASSOC OF ELEC  
 COOPS  
 Address KENTUCKY ASSOC OF ELEC  
 COOPS, 4300 CHAMPIONS TRACE  
 LN, , LOUISVILLE, Kentucky, 40218,  
 United States  
 Sales Org. ABB Installation Products USA  
 Sales Distribution  
 Currency USD  
 As on Date 03-01-2024

Catalog No. AL1000NTN

### Product Details

UPC: 783786693108



Details: Aluminum Tin-Plated Two-Hole NEMA Lugs - straight lug, concentric 1000 kcmil AL9CU, 954 kcmil, ACSR 795 (26/7, 30/19) and 954 (45/7), installing dies 161, 292, 302, 319, 1 3/4. Length 9-11/16 inch. Pad 2-39/64 inch wide x 3-5/8 inch long x 39/64 inch thick. (2) 9/16 inch Diameter Holes on 1-3/4 inch Centers. Barrel 1-27/32 inch Diameter, Bore 4-5/8 inch Deep x 1-13/64 inch inside Diameter.

### Product Details

#### Details

Catalog No.	AL1000NTN	UPC	783786693108
Description	AL TIN 2HOLE NEMA STR LUG 1000 795	GSA Compliance	No
Std. Package Weight	1.490 LB	Discount Schedule	92
Product Family	92B	CCC	
Restock Fee		Currency	USD
Customer Reference No.		Notes	
Brand Name	HOMAC	Package Qty.	10
Minimum Order Qty.	10	Country of Origin	United States


## Specifications

### General Characteristics

Category	Wire connectors
Type	Compression Lug Two Hole
Special Features	Dual-rated. Use with Aluminum and Copper conductors. Prefilled with oxide inhibitor to prevent oxidation and keep out moisture. All lugs marked with conductor sizes and die reference for easy identification.
Application	General purpose lugs for Aluminum and Copper terminations.
Connection	Compression
Material	Aluminum
Finish	Tin Plated

### Dimensions and Classifications

Brand Name	Homac
Standard	ANSI C119.4
Size	Length 8-9/16 inches
Wire Size	1000 kcmil

  
by ABB  
[electrification.us.abb.com](https://electrification.us.abb.com)

Created On: 03/01/2024