



Representative

**Catalog Number:** AL 700 N 608  
**Product ID:** 7TAA262020R0328  
**UPC Number:** 07511417880  
**Status:** A

Aluminum Two-Hole NEMA Lugs - straight lug, 600 - 700 kcmil AL-CU, Compact 700-795, installing dies 125H, 608, 786. Length 7-5/8 inch. Pad 1-3/4 inch wide x 3-1/2 inch long x 29/64 inch thick. (2) 9/16 inch diameter holes on 1-3/4 inch centers. Barrel 3-1/16 inch x 1-1/2 inch outside Diameter. Oxide Inhibitor. Purple Cap.

- Dual-Rated for Use with Aluminum and Copper Conductors.
- Made of Aluminum for High Strength and High Conductivity.
- Prefilled with Oxide Inhibitor to Prevent Oxidation and Keep Out Moisture.
- All Lugs Marked with Conductor Size and Die References for Easy Identification.
- Meets or Exceeds ANSI C119.4 Specifications.

**North American Specifications (UNSPSC)**

UNSPSC	39121409 Wire connectors
IGCC	4543 Wire connectors
Type	Compression Lug Two Hole
Special Features	Dual Rated for use with Aluminum and Copper Conductors. Prefilled with Oxide Inhibitor. Marked with Conductor Sizes and Die Reference. Meet or Exceed ANSI C119.4 Specifications.
Application	General Purpose Lugs for Aluminum and Copper Terminations
Standard	ANSI C119.4
Size	7-3/8 inch long x 1-3/4 inch wide
Connection	Compression
Wire Size	600 to 700 kcmil ; 700 to 795 kcmil
Material	Aluminum
Insulation	None

**Packaging**

Outer Quantity	25
Outer Dimensions (inches)	13.18x7.75x7
Weight Uom	0.73 lbs. Each

**Documents / Support Tools**

Safety Data Sheet (SDS) Global	SDS-00041-TB2
--------------------------------	---------------

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
 www.tnb.com

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com