


NOTES:

- 1. FABRICATED FROM 14 GA. GALVANIZED STEEL.
- PAINTED "PAD-MOUNT GREEN" MUNSELL 7GY 3.29/1.5
 HUNTER MAX DELTA E OF 4 (CONTACT FACTORY FOR COLOR
 MATCHING STANDARDS/SWATCHES).
- 3. DESIGNED TO CONFORM TO IEEE C57.12.28.



TOLERANCES (UNLESS OTHERWISE NOTED)	
SHEARED BLANKS & FRACTIONS ±.032	
OPEN NOTCH TO SHEARED EDGE ±.032	Н
PUNCHED HOLES/SHAPES ±.003	
FORMED FLANGES ±.032	
ALL OTHER DIMENSIONS ±.015	
FINAL ASSEMBLY DRAWING DIMENSIONS ARE	
NOMINAL, REFER TO INDIVIDUAL PART/SUB	
FOR ALLOWABLE CUMULATIVE TOLERANCE	
DATE 12-14-1998 BY DRM	

CAPTIVE SPRING
LOADED SILICONE
BRONZE OR STAINLESS
STEEL PENTA BOLT

SECTION A-A
(ROTATED 180 DEGREES)

DWG NO. AM303018222

SECT PED 1P 25KV 200A 303018 R

THE DURHAM COMPANY P.D. BOX 908 722 DURHAM ROAD 122 DURHAM ROAD 123 SA ROBERTAL DR. 125 N. ROUSTRIAL DR. 125 N. RO

THIS DRAWNING IS THE PROPERTY OF THE DURHAN COPPANY AND CONTAINS PROPERTAY AND CONFEDENTIAL INFORMATION WHICH HUST NOT BE DUPLICATED, USED OR DISCLOSED OTHER THAN AS EXPRESSLY AUTHORIZED BY THE DURHAN COPPANY SECRETARIONS SUBJECT TO CHANGE WHITCH TO THE OWNER OF THE PROPERTY OF THE OWNER OF THE OWNER WHITCH TO THE OWNER OWNER OF THE OWNER O

REV	DATE	DESCRIPTION	BY	-~''
Α	5-18-1999	ADDED MOD PLT RTNR	DRM	FOR DAT
				NOMI
				AL FINA
				l Fo