

Pad Mount Primary Sectionalizing Pedestals - AM Series

200 Through 600 Ampere | 15, 25 & 35 KV | Single Phase

Single Phase												
Catalog Number	Phase	Maximum *KV Rating	Amperage Rating	Modules Installed	#Parking Stands	Gauge Of Steel	Aluminum Enclosure	Dimensions			Optional Ground Sleeve	
								H"	W"	D"	Steel	Fiberglass
AM302422221	1	15/25 KV	200 Amp	-	1	14 GA.	-	30	24	22	GS202422W	GS182422F
AM302615121	1	15 KV	200 Amp	-	1	14 GA.	-	30	26	15	GS202615W	GS182615F
AM302615121-3	1	15 KV	200 Amp	3-Way 200 Amp	1	14 GA.	-	30	26	15	GS202615W	GS182615F
AM302615121A	1	15 KV	200 Amp	-	1	-	yes	30	26	15	GS202615W	GS182615F
AM302615122	1	15 KV	200 Amp	-	2	14 GA.	-	30	26	15	GS202615W	GS182615F
AM302615122-3	1	15 KV	200 Amp	3-Way 200 Amp	2	14 GA.	-	30	26	15	GS202615W	GS182615F
AM302618121-W	1	15 KV	200 Amp	-	1	12 GA.	-	30	26	18	GS202618W	GS182618F
AM302618222	1	25 KV	200 Amp	-	2	14 GA.	-	30	26	18	GS202618W	GS182618F
AM302618222-4	1	15 KV	200 Amp	4-Way 200 Amp	2	14 GA.	-	30	26	18	GS202618W	GS182618F
AM302618222-7	1	25 KV	200 Amp	4-Way 200 Amp	2	14 GA.	-	30	26	18	GS202618W	GS182618F
AM303015121	1	15 KV	200 Amp	-	1	14 GA.	-	30	30	15	GS203015W	GS183015F
AM303015122	1	15 KV	200 Amp	-	2	14 GA.	-	30	30	15	GS203015W	GS183015F
AM303015122-4	1	15 KV	200 Amp	4-Way 200 Amp	2	14 GA.	-	30	30	15	GS203015W	GS183015F
AM303015122-LW4	1	15 KV	200 Amp	4-Way 200 Amp	2	12 GA.	-	30	30	18	GS203018W	GS183018F
AM303018122-MPW	1	15 KV	200 Amp	-	2	12 GA.	-	30	30	18	GS203018W	GS183018F
AM303018221	1	15/25 KV	200 Amp	-	1	14 GA.	-	30	30	18	GS203018W	GS183018F
AM303018221-3	1	15 KV	200 Amp	3-Way 20 Amp	1	14 GA.	-	30	30	18	GS203018W	GS183018F
AM303018221-A	1	15/25 KV	200 Amp	-	1	-	yes	30	30	18	GS203018W	GS183018F
AM303018221-W	1	15/25 KV	200 Amp	-	1	12 GA.	-	30	30	18	GS203018W	GS183018F
AM303018222	1	15/25 KV	200 Amp	-	2	14 GA.	-	30	30	18	GS203018W	GS183018F
AM303018222-7	1	25 KV	200 Amp	4-Way 200 Amp	2	14 GA.	-	30	30	18	GS203018W	GS183018F
AM303018222A	1	15/25 KV	200 Amp	-	2	-	yes	30	30	18	GS203018W	GS183018F
AM303022122-MP	1	15 KV	200 Amp	-	2	14 GA.	-	30	30	22	GS203022W	GS183022F
AM303022261	1	15/25 KV	200/600 Amp	-	1	14 GA.	-	30	30	22	GS203022W	GS183022F
AM303022261-W	1	15/25 KV	200/600 Amp	-	1	12 GA.	-	30	30	22	GS203022W	GS183022F
AM303022262	1	15/25 KV	200/600 Amp	-	2	14 GA.	-	30	30	22	GS203022W	GS183022F
AM303023262-A	1	15/25 KV	200/600 Amp	-	2	-	yes	30	30	23	GS203023W	GS183023F
AM303024262	1	15/25 KV	200/600 Amp	-	2	14 GA.	-	30	30	24	GS203024W	GS183024F

Industry Standard IEEE 386 2 Thru 4-Way Small Interface Junctions - "Max Design" 15/25 KV 200/600 Amp, 15/25KV 200 Amp.

Contact factory for compatibility on special mixed multi-Point "custom" molded type or Large Interface Junctions.

Contact the factory for KV35 information.

- *Note: 25 KV 200 ampere units will accept some 200 ampere 35KV rated junctions, contact factory for details.
- 25KV units will accommodate 15KV modules and 600 ampere units will accommodate 200 ampere modules.
- -W equals 12Ga. steel - Western Underground approved.
- Contact factory for 2, 3 & 4-way 600 ampere modules.
- G-90 galvanized steel.
- Conforms to IEEE C57.27.28 Integrity.
- Powder TGIC Polyester Paint Finish, Munsell 7GY 3.29/1.5 Green.

Units supplied with modules from the factory have the below added digits.

2-Way 15 KV, 200 Amp = 2
 3-Way 15 KV, 200 Amp = 3
 4-Way 15 KV, 200 Amp = 4
 4-Way 15 KV, 200 Amp = 5

2-Way 25 KV, 200 Amp = 5
 3-Way 25 KV, 200 Amp = 6
 4-Way 25 KV, 200 Amp = 7