



Catalog No. ASL4/0NTN

Product Details

UPC: 783786696536

Details: Tin Plated Aluminum Two-Hole NEMA Lugs - Stacking lug, 4/0 Stranded AL9CU - UL listed, 250 Compact. Installing dies TX, 71H, W660, U28ART. Use VC 5 or VC 6 Tools for #2 - 4/0 Stranded. Length 5-59/64 inch. Pad 1-3/16 inch wide x 3 inch long x 19/64 inch thick. (2) 9/16 inch holes on 1-3/4 inch Centers. Barrel 1-15/16 inch long x 7/8 inch Outside Diameter. Oxide Inhibitor. White Cap.



Product Details

Details

|                        |                                 |
|------------------------|---------------------------------|
| Catalog No.            | ASL4/0NTN                       |
| Description            | AL TIN 2HOLE NEMA STACK LUG 4/0 |
| Std. Package Weight    | 0.220 LB                        |
| Product Family         | 92B                             |
| Restock Fee            |                                 |
| Customer Reference No. |                                 |
| Brand Name             | HOMAC                           |
| Minimum Order Qty.     | 1                               |

|                                |                                                   |
|--------------------------------|---------------------------------------------------|
| UPC                            | 783786696536                                      |
| GSA Compliance                 | No                                                |
| Discount Schedule              | 92                                                |
| CCC                            |                                                   |
| Currency                       | USD                                               |
| Notes                          | No standard price available. Book price displayed |
| Package Qty.                   | 1                                                 |
| Country Or Territory Of Origin | United States                                     |

General Characteristics

|                  |                                                                                                                                                                                                                                                                                        |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category         | Wire connectors                                                                                                                                                                                                                                                                        |
| Special Features | Made from Aluminum which provides high strength and high conductivity. Dual-rated. Use with Aluminum and Copper conductors. Prefilled with oxide inhibitor to prevent oxidation and keep out moisture. All lugs marked with conductor sizes and die reference for easy identification. |
| Application      | General purpose lugs for Aluminum and Copper terminations.                                                                                                                                                                                                                             |
| Connection       | Compression                                                                                                                                                                                                                                                                            |
| Material         | Aluminum                                                                                                                                                                                                                                                                               |
| Finish           | Tin Plated                                                                                                                                                                                                                                                                             |

Dimensions and Classifications

|            |                                     |
|------------|-------------------------------------|
| Brand Name | Homac                               |
| Standard   | ANSI C119.4<br>ANSI C119.4          |
| Size       | Length 6 inches X 1-15/64 inch wide |
| Wire Size  | 4/0 AWG                             |

