


## Compression Connectors

Made of high-conductivity seamless aluminum tubing, tin plated for corrosion resistance.

### Type ATL — Aluminum Two-Hole Lugs

- Specifically designed for use with aluminum or copper conductor (concentric, compressed or compact)
- Made of high-conductivity seamless aluminum tubing
- Tin plated for corrosion resistance
- Chamfered barrels for ease of installation
- Can be used for high-voltage application up to 35kV, provided high-voltage insulation techniques are used
- Color coded for quick, easy die identification
- Prefilled with oxide-inhibiting compound
- UL® Listed when installed with Blackburn®, Burndy®, T&B® or Anderson tools




CAT. NO.	CONDUCTOR SIZE (CU)	STUD SIZE	DIMENSIONS (IN.)							DIE COLOR CODE
			A	B	C	D	L	W	T	
ATL102-38	1/0 Str. AWG	3/8	1 1/32	2 1/16	3/8	1	3 13/32	1/8	3/16	TAN
ATL102	1/0 Str. AWG	1/2	1 3/16	3	1/2	1 1/4	4 1/16	1 5/16	3/16	OLIVE
ATL202	2/0 Str. AWG		1 1/16	3 3/8	3/4	1 1/4	5	3 3/32	7/32	RUBY
ATL302	3/0 Str. AWG		1 1/32	3 3/8	3/4	1 1/4	5 5/32	1 1/16	1/2	WHITE
ATL402	4/0 Str. AWG		1 1/8	3	1/2	1 1/4	5 5/8	1 1/16	1/4	RED
ATL2502	250 kcmil		2 1/32	3	1/2	1 1/4	5 25/32	1 9/32	1/4	BLUE
ATL3002	300 kcmil		2	3	1/2	1 1/4	5 5/8	1 1/8	5/32	BROWN
ATL3502	350 kcmil		2 1/16	3	1/2	1 1/4	6 1/16	1 1/2	5/16	GREEN
ATL4002	400 kcmil		2 1/16	3	1/2	1 1/4	6 1 1/16	1 5/8	3/8	PINK
ATL5002	500 kcmil		2 1/16	3	1/2	1 1/4	6 1 1/16	1 29/32	3/8	BLACK
ATL6002	600 kcmil		2 1/16	3	1/2	1 1/4	6 1 3/16	1 29/32	1 1/32	N/A
ATL7502	750 kcmil		2 1/8	3	1/2	1 1/4	7 1/8	2 1/8	3/8	N/A

Chamfered barrels enable easier installation.

### Type ASP – Aluminum Splices

- Specifically designed for use with aluminum-to-aluminum, aluminum-to-copper or copper-to-copper conductor (concentric, compressed or compact)
- Made of high-conductivity seamless aluminum tubing
- Tin plated for corrosion resistance
- Chamfered barrels for ease of installation
- Can be used for high-voltage application up to 35kV, provided high-voltage insulation techniques are used
- Color-coded for quick, easy die identification
- Prefilled with oxide-inhibiting compound
- UL® Listed when installed with Blackburn®, Burndy®, T&B® or Anderson tools



CAT. NO.	CONDUCTOR SIZE (AL OR CU)	LENGTH L (IN.)	DIE COLOR CODE
ASP8	#8 Str. AWG	1 1/4	BLUE
ASP6	#6 Str. AWG	1 5/8	GRAY
ASP4	#4 Str. AWG	1 7/8	GREEN
ASP2	#2 Str. AWG	1 3/4	PINK
ASP1	#1 Str. AWG	2 1/8	GOLD
ASP10	1/0 Str. AWG	2 3/8	TAN
ASP20	2/0 Str. AWG	2 1/2	OLIVE
ASP30	3/0 Str. AWG	2 7/8	RUBY
ASP40	4/0 Str. AWG	3 1/4	WHITE
ASP250	250 kcmil	4	RED
ASP300	300 kcmil	4	BLUE
ASP350	350 kcmil	3 3/8	BROWN
ASP400	400 kcmil	4 1/8	GREEN
ASP500	500 kcmil	5	PINK
ASP600	600 kcmil	5 1/8	BLACK
ASP750	750 kcmil	5 3/8	BLACK
ASP1000	1,000 kcmil	6	N/A

