

BRONZE
BC/BH

# HOT LINE TAP CLAMPS BRONZE

For Copper conductor.

Designed for standard "hot stick" application.



FIGURE 1    FIGURE 1A    FIGURE 2    FIGURE 3

**Material:** **Body and Keeper** - BC/BH—Brass Alloy  
BC/BH—FTP—Brass Alloy  
— Tin Plated

**Eyebolt** - Bronze Alloy

**Eyestem** - Bronze Alloy or Stainless Steel

**Washer** - BH—Silicon Bronze  
BC/BH—FTP—Stainless Steel

1. BC20LD has a longer "DUCKBILL" for easier attachment to a stirrup bail or conductor.
2. For connector with inhibitor in main jaw and plastic bag, add suffix "XB" to catalog number.




FIGURE 1 & 1A (BC & BC-LD)




FIGURE 2 (BH)




FIGURE 3 (S1530CC/S1540CC)

## Product Data & Conductor Size

CATALOG NUMBER	MAIN LINE	TAP	FIG. NO.	PLATING	PACKAGING	CONDUCTOR RANGE (AWG OR KCMIL)		DIMENSIONS INCHES (MM)			AP-PROX. WT. EACH LBS. (KG.)
						MAIN	TAP	D	L	H	
BC20**	CU	CU	1	None	Box	#8 Sol - 2/0 Str. .128" - .419" (3.25 - 10.64)	#8 Sol - 2/0 Str. .128" - .414" (3.25 - 10.51)	.78 (19.81)	1-1/4 (31.7)	5.0 (127.0)	0.7 (.32)
BC20XB**	CU	CU		None	Inhib & Bag						
BC20FTP	CU	CU		Tin plated	Box						
BC20FTPXB	CU	CU		Tin plated	Inhib & Bag						
BC20LD	CU	CU	1A	None	Box						
BC20LDXB	CU	CU		None	Inhib & Bag						
BC20LDFTP	CU	CU		Tin Plated	Box						
BC20LDFTPXB	CU	CU		Tin Plated	Inhib & Bag						
BH4	CU	CU	2	None	Box	#6 Sol - 400mcm .162" - .745" (4.12 - 18.96)	#6 Sol - 4/0 Str. .162" - .547" (4.12 - 13.89)	-	1-3/8 (34.92)	6-3/4 (171.45)	1.71 (.78)
BH4XB	CU	CU		None	Inhib & Bag						
BH4FTP	CU	CU		Tin plated	Box						
BH4FTPXB	CU	CU		Tin plated	Inhib & Bag						
*S1530CC	CU	CU	3	None	Box	#6 Sol - 400mcm .162" - .745" (4.12 - 18.96)	#6 Sol - 4/0 Str. .162" - .547" (4.12 - 13.89)	-	1-3/8 (34.92)	6-3/4 (171.45)	1.59 (.72)
*S1530GP	CU	CU		Tin plated	Box						
*S1540CC	CU	CU		None	Box						
*S1540GP	CU	CU		Tin plated	Box						
						4/0 Str. - 800mcm .502" - 1.031" (12.78 - 26.24)	#4 Sol - 350mcm .198" - .703" (5.04 - 17.98)		1-7/8 (48)	8-1/4 (210)	2.03 (.92)

\*For factory grease, replace "S" prefix with "P".

\*\*RUS Listed